



DB LINK LUX LIGHTING



LED Light Bar

DBLE50C

• 50" Straight Combination LED Light Bar • 96 - 3 Watt High Output LED's • 288 Watts • 10V-24V DC Operating Voltage • 14750 Lumens • Shock Proof Electronics • Shatter Proof Polycarbonate Lens • Black Extruded Aluminum Chassis • IP67 Element Rating • Harness Sold Separately



LED Light Bar

DBLE42C

• 42" Straight Combination LED Light Bar • 80 - 3 Watt High Output LED's • 248 Watts • 10V-24V DC Operating Voltage • 12250 Lumens • Shock Proof Electronics • Shatter Proof Polycarbonate Lens • Black Extruded Aluminum Chassis • IP67 Element Rating • Harness Sold Separately



LED Light Bar

DBLE32C

• 32" Straight Combination LED Light Bar • 60 - 3 Watt High Output LED's • 180 Watts • 10V-24V DC Operating Voltage • 9200 Lumens • Shock Proof Electronics • Shatter Proof Polycarbonate Lens • Black Extruded Aluminum Chassis • IP67 Element Rating • Harness Sold Separately



LED Light Bar

DBLE12C

• 12" Straight Combination LED Light Bar • 20 - 3 Watt High Output LED's • 60 Watts • 10V-24V DC Operating Voltage • 3000 Lumens • Shock Proof Electronics • Shatter Proof Polycarbonate Lens • Black Extruded Aluminum Chassis • IP67 Element Rating • Harness Sold Separately



LED Light Bar

DBLE8C

• 8" Straight Combination LED Light Bar • 12 - 3 Watt High Output LED's • 36 Watts • 10V-24V DC Operating Voltage • 1850 Lumens • Shock Proof Electronics • Shatter Proof Polycarbonate Lens • Black Extruded Aluminum Chassis • IP67 Element Rating • Harness Sold Separately



Square Flush Mount Flood

DBLXFW3.0F

• 3" High Power LED Flood Light • 4 - 5 Watt High Output LED's • 20 Watts • 10V-24V DC Operating Voltage • 1200 Lumens • Shock Proof Electronics • Black Extruded Aluminum Chassis • IP67 Element Rating • Harness Sold Separately



LED Bar Connection Harness

DBLXH1

• The Lighting Solutions Wiring Harnesses are Designed to Connect a Single or Dual LED Light System to your 12V Power Supply. They feature an Inline Fuse Holder, a Pre-Wired 12Volt Relay, and a Push Button On-Off Switch. The Harnesses are Compatible with any of the Surface Mount or Dual Row LED Bars





RGB LIGHTBARS, CUBE LIGHTS & ROCK LIGHTS



DBLB22RGB - 22" RGB* LIGHT BAR

- 7600 Lumens • High power CREE LED light bar • Combination spot/ flood lighting pattern • IP67 element rating • High output cree LED's • Black extruded aluminum chassis • Harness and RGB Harness Sold Separately



DBLB14RGB - 14" RGB* LIGHT BAR

- 4560 Lumens • High power CREE LED light bar • Combination spot/ flood lighting pattern • IP67 element rating • High output cree LED's • Black extruded aluminum chassis • Harness and RGB Harness Sold Separately



DBLB8RGB - 8" RGB* LIGHT BAR

- 2280 Lumens • High power CREE LED light bar • Combination spot/ flood lighting pattern • IP67 element rating • High output cree LED's • Black extruded aluminum chassis • Harness and RGB Harness Sold Separately



DBSM4D-K-RGB - 4" RGB* CUBES -Sold as Pairs

- 1080 Lumens • High power CREE LED Cube • IP67 element rating • High output cree LED's • Black extruded aluminum chassis • Harness and RGB Harness Sold Separately



DBSMRGB-4-ROCK LIGHTS

- Accent Surface Light Pattern • (4) 3 - 0.5W High Power LEDs • 6W total output • Operating Voltage: 10- 30 VDC • 30,000 Hours AVG Lifespan
- Die-cast aluminum extrusion • Shock Proof Electronics • Polycarbonate Lens
- Flat Surface and Tube Mounting Bases

*MUST PURCHASE *RGBC-8* CONTROL MODULE TO USE RGB FUNCTIONS (SOLD SEPARATELY)

- Territory Restrictions -