



3XL Series Subwoofers

- DDC Non-pressed Raw Pulp Cone • High Roll Nitrile Butadiene Rubber (NBR) Surround • 3.5" Vented HD BASV Voice Coil Former • Perimeter Aero-Vent Voice Coil Cooling Vents • Non Resonance DDC Coated Cast Aluminum Basket
- XTRA XTRA XTRA Large Triple Stacked Motor Structure
- Square Spring Loaded Nickel Plated Push Terminals



Model	Size	RMS/Peak	Voice Coil	Impedance
3XL-1520D	15"	1500Watts/3000Watts	3.5"	Dual 2Ω
3XL-1510D	15"	1500Watts/3000Watts	3.5"	Dual 1Ω
3XL-1220D	12"	1000Watts/2000Watts	3.5"	Dual 2Ω
3XL-1210D	12"	1000Watts/2000Watts	3.5"	Dual 1Ω

2XL Series Subwoofers

- Woven Glass Fiber Cone With Pressed Kraft Paper Reinforcement • Nitrile Butadiene Rubber (NBR) Surround • 2.5" Vented BKS Voice Coil Former
- Perimeter Aero-Vent Voice Coil Cooling Vents • Non Resonance DDC Coated Cast Aluminum Basket • XTRA XTRA Large Double Stacked Motor Structures • Square Spring Loaded Nickel Plated Input Terminals



Model	Size	RMS/Peak	Voice Coil	Impedance
2XL-1240D	12"	450Watts/900Watts	2.5"	Dual 4Ω
2XL-1040D	10"	400Watts/800Watts	2.5"	Dual 4Ω

XL Series Shallow Subwoofers

- Proprietary Single Piece Injection Molded Flat Cone Design
- High Roll Santoprene® Surround • 2.0" Vented KSV Voice Coil Former • Perimeter Aero-Vent Voice Coil Cooling Vents
- Proprietary Non Resonance Polycarbonate/Glass Fiber Basket
- Chrome Push Terminals



Model	Size	RMS/Peak	Voice Coil	Impedance
XL-1240TD	12"	400Watts/800Watts	2.5"	Dual 4Ω
XL-1240T	12"	400Watts/800Watts	2.5"	Single 4Ω
XL-1040TD	10"	350Watts/700Watts	2.5"	Dual 4Ω
XL-1040T	10"	350Watts/700Watts	2.5"	Single 4Ω



XL Series Subwoofers

- Proprietary Non-pressed Paper DDC Coated Cone • High Roll Santoprene® Surround • 2.0" Vented BASV Voice Coil Former
- Perimeter Aero-Vent Voice Coil Cooling Vents • Proprietary Non Resonance Polycarbonate/Glass Fiber Basket • Chrome Push Terminals



Model	Size	RMS/Peak	Voice Coil	Impedance
XL-1240D	12"	400Watts/800Watts	2.0"	Dual 4Ω
XL-1240	12"	400Watts/800Watts	2.0"	Single 4Ω
XL-1040D	10"	350Watts/700Watts	2.0"	Dual 4Ω
XL-1040	10"	350Watts/700Watts	2.0"	Single 4Ω
XL-840D	8"	200Watts/400Watts	2.0"	Dual 4Ω
XL-840	8"	200Watts/400Watts	2.0"	Single 4Ω

L Series Subwoofers

- Injection Molded PP Cone • Large Roll NBR (Nitrile) Rubber Surround • 2.5" Vented BKS Voice Coil Former • Perimeter Aero-Vent Voice Coil Cooling Vents • Non Resonance DDC Coated Stamped Steel Basket • Rubber Mounting Gasket/Trim Ring • Chrome Push Terminals



Model	Size	RMS/Peak	Voice Coil	Impedance
L-1504D	15"	500Watts/1000Watts	2.5"	Dual 4Ω
L-1204D	12"	400Watts/800Watts	2.5"	Dual 4Ω
L-1004D	10"	350Watts/700Watts	2.5"	Dual 4Ω

M Series Subwoofers

- Proprietary 4-layer Non-pressed Paper DDC Finish Cone Dynamic Damping Coating (DDC) • Large Roll NBR Rubber Surround • Chrome Push Terminals • Non-Resonant Basket



Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
M-1504D	15"	425Watts/850Watts	2.5" BASV	Dual 4Ω	220 oz.
M-1504	15"	425Watts/850Watts	2.5" BASV	Single 4Ω	220 oz.
M-1204D	12"	375Watts/750Watts	2" BASV	Dual 4Ω	164 oz.
M-1204	12"	375Watts/750Watts	2" BASV	Single 4Ω	164 oz.
M-1004D	10"	325Watts/650Watts	2" BASV	Dual 4Ω	158 oz.
M-1004	10"	325Watts/650Watts	2" BASV	Single 4Ω	158 oz.



S Series Thin Subwoofers

- Injection Molded Cone • Composite Fiber Basket
- Chrome Push Input Terminals • 3.25" Deep



Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
S-12TD	12"	300Watts/600Watts	2" KSV	Dual 4Ω	140 oz.
S-12T	12"	300Watts/600Watts	2" KSV	Single 4Ω	140 oz.
S-10TD	10"	275Watts/550Watts	2" KSV	Dual 4Ω	116 oz.
S-10T	10"	275Watts/550Watts	2" KSV	Single 4Ω	116 oz.

S Series Subwoofers

- 4 Layer Black Paper/Wool Cone • Large Roll Foam Surrounds
- Chrome Push Input Terminals • Pole and Aero Vented Cooling
- Non-Resonant Basket



Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
S-1204D	12"	300Watts/600Watts	2" BASV	Dual 4Ω	142 oz.
S-1204	12"	300Watts/600Watts	2" BASV	Single 4Ω	142 oz.
S-1004D	10"	275Watts/550Watts	2" BASV	Dual 4Ω	116 oz.
S-1004	10"	275Watts/550Watts	2" BASV	Single 4Ω	116 oz.
S-84D	8"	125Watts/250Watts	1.5" BASV	Dual 4Ω	116 oz.
S-84	8"	125Watts/250Watts	1.5" BASV	Single 4Ω	116 oz.

PS Series Subwoofers

- DDC Treated Paper Cone • 4 Layer Treated Foam Surround
- 2" BASV Voice Coil Former • Stamped Steel Basket



Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
PS-12	12"	250Watts/500Watts	2" KSV	Single 4Ω	140 oz.
PS-10	10"	200Watts/400Watts	2" KSV	Single 4Ω	140 oz.



L Series Full & Mid Range Coaxial Speakers

• PP Cone • Steel Basket



Model	Size	RMS/Peak	Tweeter
L2-700	7"	90Watts/270Watts	-
L2-693	6 x 9"	100Watts/300Watts	0.75"
L2-692T	6 x 9" Thin	60Watts/180Watts	0.75"
L2-682	6 x 8"	70Watts/210Watts	0.75"
L2-675	6.75"	60Watts/180Watts	0.75"
L2-652	6.5"	60Watts/180Watts	0.75"
L2-522	6.25"	50Watts/150Watts	0.75"
L2-462	4 x 6"	40Watts/120Watts	0.75"

S Series Full Range Coaxial Speakers and Components

• DDC Paper Cone • Black Painted Steel Basket



Model	Size	RMS/Peak	Tweeter	Magnet
S-6903	6 x 9" 3-Way	70Watts/210Watts	0.75" & 2" Mylar Cone	20 oz.
S-6902T	6 x 9" Thin	50Watts/150Watts	0.75" Silk Dome	10 oz.
S-6802	6 x 8" (5x7" Compatible)	60Watts/180Watts	0.75" Silk Dome	10 oz.
S-4102	4 x 10"	50Watts/150Watts	0.75" Silk Dome	10 oz.
S-6502	6.5"	50Watts/150Watts	0.75" Silk Dome	10 oz.
S-6752	6.75"	50Watts/150Watts	0.75" Silk Dome	10 oz.
S-6502T	6.5" (Thin)	45Watts/135Watts	0.75" Silk Dome	10 oz.
S-5202	5.25"	40Watts/120Watts	0.75" Silk Dome	8 oz.
S-4602	4 x 6"	35Watts/105Watts	0.5" PEI	6 oz.
S-4002	4"	35Watts/105Watts	0.75" Silk Dome	6 oz.
S-3502	3.5"	30Watts/90Watts	0.5" PEI	4 oz.
S-275CF	2.75" (Full Range)	30Watts/60Watts	-	3 oz.



Component Kits and Tweeters



Model	Size	RMS/Peak	Tweeter	Magnet
L2-6C	6.5" Component w/X-over Kit	75Watts/225Watts	1" Aluminum Dome	8.6 oz.
S-60C	6.5" Component w/X-over Kit	70Watts/210Watts	1" Silk Dome	10 oz.
S-50C	5.25" Component w/X-over Kit	50Watts/150Watts	1" Silk Dome	10 oz.
L-1A	1" Aluminum Dome Tweeter	50Watts/100Watts	1" Aluminum Dome	Neodymium
S-1S	1" Silk Dome Tweeter	50Watts/100Watts	1" Silk Dome	Neodymium
S-1ZT	1" Zirconium Super Tweeter	100Watts/200Watts	1" Zirconium	-
L-3H	3" Compression Horn Tweeter	100Watts/200Watts	Die Cast Horn	18 oz.

XMA Mini Amplifiers

- Ultra Low Current Draw • Double Sided Copper Plated PCB
- PWM MOSFET Power Supply • Digital Sound Optimization Circuitry
- High Damping Control Circuit • Variable Subsonic Filter
- High Current Voltage Ripple Rejection Circuitry • Balanced RCA Inputs
- Auto Turn On/Off • Remote Soft Delay Turn On/Off Circuit • 40 Click Variable Low Pass Electronic Crossover • 40 Click Variable Frequency/18dB Bass Boost EQ • Variable Gain Control



Model	Channels	Power	Peak
XMA -3000D	1	150 Watts x 4 + 500 Watts x 1	2200 Watts
XMA- 2000D	1	100 Watts x 4 + 400 Watts x 1	1600 Watts
XMA- 1205D	1	200 Watts x 4	1600 Watts
XMA- 5900IR	5	100 Watts x 4	800 Watts
XMA- 4250IR	4	400 Watts x 2	1600 Watts
XMA- 2405IR	2	300 Watts x 2	1200 Watts
XMA- 2200IR	2	200 Watts x 2	800 Watts

Full Range Class A/B Amplifiers

- MOSFET Power Supply • Variable High/Low Level Input
- Variable Bass Boost • Variable Gain Control • Stable at 2 Ohm



Model	Channels	Power	Peak
ASA3-1100.5	4+1	150 Watts x 4 + 500 Watts x 1	2200 Watts
ASA3-700.5	4+1	100 Watts x 4 + 400 Watts x 1	1600 Watts
ASA3-600.4	4	200 Watts x 4	1600 Watts
ASA3-400.4	4	100 Watts x 4	800 Watts
ASA3-800.2	2	400 Watts x 2	1600 Watts
ASA3-600.2	2	300 Watts x 2	1200 Watts
ASA3-400.2	2	200 Watts x 2	800 Watts
ASA3-300.2	2	150 Watts x 2	600 Watts
ASA3-200.2	2	100 Watts x 2	400 Watts



Mono-Block Class A/B Amplifiers



- MOSFET Power Supply • Variable High/Low Level Input
- Variable Bass Boost • Variable Gain Control • Stable at 2 Ohm

Model	Channels	Power	Peak
ASA3-600.1	1	600 Watts x 1	1200 Watts
ASA3-400.1	1	400 Watts x 1	800 Watts

Mono-Block Class D Amplifiers

Model	Channels	Power	Peak
ASA3-1500.1D	1	1500 Watts x 1	3000 Watts
ASA3-1000.1D	1	1000 Watts x 1	2000 Watts

XL Mini Amplifiers

- Wrap Around Aluminum Heatsink • Conformal Coated PC Board • Variable Gain Control • Auxiliary Input (3.5mm) • Variable Subwoofer EQ



Model	Channels	Power	Peak	Remote Gain
XL-2205M	2	200 Watts x 2 (2Ω)	800 Watts	-
XL-4165M	4	160 Watts x 4 (2Ω)	1280 Watts	-
XL-355DM	1	350 Watts x 1 (2Ω)	700 Watts	Yes
XL-605DM	1	600 Watts x 1 (2Ω)	1200 Watts	Yes
XL-3515M	3	160 Watts x 4 (2Ω)	1340 Watts	-
XL-5675M	5	160 watts x 4 + 350 watts x 1 (2Ω)	1980 Watts	-

Powersports Soundbars



XL-1200



- 12 Speaker 500 Watt Amplified Bluetooth Powersports Soundbar • 6 x 3.5" Square Poly Cone Woofers • 2 x 3" Full Range Marine Grade Poly Cone Speakers • 4 x 1" SD Mylar Tweeters • Heavy Duty Extruded Aluminum Water Tight Housing
- LED back-lit Control Panel • LED Visual Notifications • Audible Power On/Off Notifications • Built In DSP Processor w/Distortion Limiter • Bluetooth and Wired Inputs • 2 Volt Line Output • Auto Turn On/Off Circuit



Powersports Soundbars



XL-1000

- 10 Speaker 400 Watt Amplified Bluetooth Powersports Soundbar • 8 x 3" Full Range Marine Grade Poly Cone Speakers • 2 x 1.25" SD Mylar Tweeters • Heavy Duty Extruded Aluminum Water Tight Housing • LED back-lit Control Panel • LED Visual Notifications
- Audible Power On/Off Notifications • Built In DSP Processor w/Distortion Limiter • Bluetooth and Wired Inputs • 2 Volt Line Output
- Auto Turn On/Off Circuit



XL-800

- 8 Speaker 300 Watt Amplified Bluetooth Powersports Soundbar • 6 x 3" Full Range Marine Grade Poly Cone Speakers • 2 x 1.25" SD Mylar Tweeters • Heavy Duty Extruded Aluminum Water Tight Housing • LED backlit Control Panel • LED Visual Notifications • Audible Power On/Off Notifications • Built In DSP Processor w/Distortion Limiter • Bluetooth and Wired Inputs • 3 Volt Line Output • Auto Turn On/Off Circuit