



Subwoofer Series

Common Features:

- 2" Hi-Temperature 4 Layer Voice Coil • Hyper Excursion Motor & Suspension
- Poly-Injected Inverted Cone • Protective Rubber Magnet Boot



Model	Size	Max Power	Impedance
BIW10S4	10"	1500 Watts	Single 4Ω
BIW10D4	10"	1500 Watts	Dual 4Ω
BIW12S4	12"	1500 Watts	Single 4Ω
BIW12D4	12"	1500 Watts	Dual 4Ω

Loud Speaker Series

Common Features:

- Silver Poly-Injected Cone • Rubber Butyl Surround • 1.25" Mylar Dome Mid-Range • Nominal Impedance 4 ohms

- BI69** – 2.5" Paper Dome Mid-Range • (2) 1" Piezo Dome Tweeters



Model	Size	Max Power	Speaker Sensitivity
BI40	4" – 4-Way Speaker	150 Watts	89 dB
BI46	4" x 6" – 4-Way Speaker	150 Watts	89 dB
BI50	5.2" – 4-Way Speaker	200 Watts	91 dB
BI57	5" x 7" – 4-Way Speaker	200 Watts	91 dB
BI60	6.5" – 4-Way Speaker	300 Watts	92 dB
BI69	6" x 9" – 4-Way Speaker	300 Watts	91 dB

Component Set

- Silver Poly-Injected Cone • Rubber Butyl Surround
- 1" Dome Component Tweeters • Nominal Impedance 4 ohms



Model	Size	Max Power	Speaker Sensitivity
BI65C	6.5" – 4-Way Speaker	300 Watts	92 dB