



Rebel Series Subwoofers

- Powder Coated Stamped Solid Steel Basket • Poly-glass Fiber Caped UV Treated Paper Cone • Dual Wave Roll Surrounds • Dual 4" and 2" CCAW Voice Coils on an Aluminum Former with Reinforced Neck Joints • High Ferrite Stacked Magnets
- 5-Way Binding Posts with Push or Banana Nickel Plated Terminals

Model	Size	Power RMS/Peak	Impedance	Magnet
REBEL 10	10"	500W/1000W	Dual 4 ohm	65 oz.
REBEL 12	12"	500W/1000W	Dual 4 ohm	65 oz.
REBEL 15	15"	500W/1000W	Dual 4 ohm	65 oz.



V Series Subwoofers

- Stamp Steel Basket • Polymica Cone with Woven Glass Fiber Dust Cap
- 1.5" Four Layer Voice Coil with Aluminum Former and Reinforce Neck Joint • 1" N-Roll Polyester Foam Surround

Model	Size	Power RMS/Peak	Impedance	Magnet
V10	10"	250W/500W	Dual 4 ohm	40 oz.
V12	12"	250W/500W	Dual 4 ohm	40 oz.
V122	12"	250W/500W	Dual 2 ohm	40 oz.



TW Series Subwoofers

- Stamp Steel Basket • Finger "V" Ultra Light Cone • 2.5" Voice Coil
- 1" Tall Santoprene Surround • Woven Silver Plated Tinsel Leads • Push-In or Banana for 8 AWG Terminals

Model	Size	Power RMS/Peak	Impedance	Magnet
TW10	10"	500W/1000W	Dual 4 ohm	80 oz.
TW12	12"	500W/1000W	Dual 4 ohm	80 oz.
TW15	15"	500W/1000W	Dual 4 ohm	80 oz.



DC Series Subwoofers

- Aluminum Die-Cast Basket • Finger "V" Ultra Light Cone • 2.5" Voice Coil
- 1" Tall Santoprene Surround • Woven Silver Plated Tinsel Leads • Push-In or Banana Nickel Plated Terminals

Model	Size	Power RMS/Peak	Impedance	Magnet
DC10	10"	600W/1200W	Dual 4 ohm	120 oz.
DC12	12"	600W/1200W	Dual 4 ohm	120 oz.





V Series Coaxial Speakers

- Heavy Gauge Steel/Low Resonance Composite Baskets • UV Protected Poly Injected Cones • Copper Voice Coils • Butyl Rubber Surrounds • Fully Isolated Tinsel Leads • Custom 2-Piece Paintable Grills

Model	Size	Power RMS/Peak	Impedance	Tweeter
VX5	5.25", 2-Way	50W/200W	4 ohm	20mm Silk Dome
VX6	6.5", 2-Way	60W/250W	4 ohm	20mm Silk Dome
VX68	5x7"/6x8", 2-Way	60W/250W	4 ohm	20mm Silk Dome
VX69	6x9", 3-Way	70W/300W	4 ohm	2" Mid/13mm Mylar



V Series Component Speakers (2-Way)

VK6

- 6.5" 4 ohm Speaker • Heavy Gauge Steel/Low Resonance Composite Baskets • UV Protected Polymica Injected Cones • Copper Voice Coils • Butyl Rubber Surrounds • Handle 60-250 Watts • 12 Db Crossovers • 20mm Silk Soft Dome Swivel Tweeters • Fully Isolated Tinsel Leads • Custom 2-Piece Paintable Grills



Slim Series Component Speakers

- SLIM SERIES Stage II Component Speakers • Compact Size • Steel Basket • Polymica Cone • Shallow Mounting • 12 Db External Crossover • 20mm Silk Soft Dome Tweeter

Model	Size	Power RMS/Peak	Impedance
SK5II	5.25", 2-Way	90W/210W	4 ohm
SK6II	6.5", 2-Way	100W/220W	4 ohm



Components/ Convertibles Speakers

- Cast Basket • Carbon Fiber Cones • 28mm Silk Dome Tweeter • 18 Db External Crossover

Model	Size	Power RMS/Peak	Impedance
CK6III	6.5", 2-Way	130W/280W	4 ohm
CK6.9III	6x9", 2-Way	150W/320W	4 ohm



Tweeter

CT1A

- 25mm 4Ω Aluminum Dome Tweeter • 12 dB Crossovers • 60W RMS/120W Peak • Neodymium Magnets • Flexible Mounting Options including Surface or Flush Mount





M Series Pro Audio Speakers

Model	Description
M6	- 6" Midrange, 140 Watts RMS, 300 Watts Max, 8 ohm v.c.
M8	- 8" Midrange, 150 Watts RMS, 300 Watts Max, 8 ohm v.c.
M10	- 10" Midrange, 150 Watts RMS, 350 Watts Max, 8 ohm v.c.
M12	- 12" Midrange, 180 Watts RMS, 400 Watts Max, 8 ohm v.c.
M15	- 15" Midrange, 200 Watts RMS, 400 Watts Max, 8 ohm v.c.



M Series Pro Audio Shallow Mount

Model	Description
M6S	- 6" Midrange, 130 Watts RMS, 300 Watts Max, 4 ohm v.c.
M8S	- 8" Midrange, 140 Watts RMS, 300 Watts Max, 4 ohm v.c.



T Series Pro/Car Audio Bullet Tweeters

Model	Description
T44	- 44mm Super Tweeter, 60 Watts RMS, 300 Watts Max, 4 ohm v.c.
CT 4	- 1" VC, Titanium Magnet, Super Tweeter, 120 Watts Max, 8 ohms
CT 6	- 1.75" VC, Titanium Magnet, Super Tweeter, 120 Watts Max, 8 ohms



PAT Series Pro Audio Compression Drivers

Model	Description
PAT 1	- 1" Throat, 1" VC, Neodymium Magnet, Screw Mount Driver, 50 Watts Max, 8 ohms
PAT 2	- 1" Throat, 1" VC, Neodymium Magnet, Screw Mount Driver, 200 Watts Max, 8 ohms
PAT 34	- 34mm, Titanium Magnet, Bolt Mount Driver, 200 Watts Max, 8 ohms
PAT 50	- 1" Throat, 2" VC, 30 oz Magnet, Screw Mount Driver, 300 Watts Max, 8 ohms
PAT 50A	- 1" Throat, 2" VC, 30 oz Magnet, Bolt Mount Driver, 300 Watts Max, 8 ohms



M Series Pro Audio Shallow Mount

Model	Description
H1	- 1" Throat, Glue-on, Flair Horn for PAT 1 & 2 Drivers
F2	- 1" Baby Cheek, Bolt-on, Fiberglass Hand Laid 90 x 90 Dispersion

