



Phantom Series Amplifiers



- Micro Technology • Variable Subsonic Filter • Variable Low Pass Filter • Variable Bass Boost • 1-ohm Stable

Model	Chs/Class	4 ohm RMS	2 ohm RMS	Max Power
PH-5100MD FR	5/-	90Wx4 + 300W	120Wx4 + 600W	1000W
PH-4100 FR	4/AB	80W x 4	120W x 4	2500W
PH-4000 MD	1/D	2000W@1-ohm	-	4000W
PH-2500 MD	1/D	80W x 4	120W x 4	2500W
PH-1600 MD	1/D	800W@1-ohm	-	1600W

XD Series Amplifiers



Model	Chs/Class	4 ohm RMS	2 ohm RMS	Max Power
XD-1800.1	1/D	245W x 1	450W x 1	1800W
XD-5040.4 FR	4/AB	55W x 4	75W x 4	1400W
XD-1400.2 FR	2/AB	120W x 2	170W x 2	1400W

MR Series Marine Amplifiers



- Low Pass Filter • Subsonic Filter • Bass Boost

Model	Chs/Class	4 ohm RMS	2 ohm RMS	Max Power
MR-2500.1	1/D	-	-	2500W
MR-160.4	4/AB	80W x 4	160W x 4	-

GT Series Amplifiers



- Mosfet Power Supply • Variable Subsonic Filter • Variable Bass Boost • 5-Way Protection • High/Low Level RCA Inputs

Model	Chs	4 ohm RMS	2 ohm RMS	Max Power
GT-3000.2	2	500W x 2	700W x 2	3000W
GT-2000.2	2	300W x 2	500W x 2	2000W
GT-1700.2	2	150W x 2	200W x 2	1700W
GT-1200.4	4	100W x 4	150W x 4	1200W
GT-950.4	4	60W x 4	90W x 4	9500W
GT-900.2	2	100W x 2	150W x 2	9000W



XFL Series Subwoofers

- DVC 4-ohm Impedance • Cast Frame • 3" High-Temp Voice Coil • 200 oz. Magnet

Model	Size	RMS/Peak Power
XFL-1544	15"	1000W/2000W
XFL-1244	12"	1000W/2000W
XFL-1044	10"	1000W/2000W

Available in DVC 2-ohm Impedance



TNT Series Subwoofers

- DVC 4-ohm Impedance • Cast Frame • 2.5" High Temp Voice Coil • 120 oz. Magnet

Model	Size	RMS/Peak Power
TNT-1244	12"	600W/1200W
TNT-1044	10"	600W/1200W



XD Series Subwoofers

- DVC 4-ohm Impedance • Stamped Steel Basket
- 2" High-Temp Voice Coil (1.5" XD-6.5)

Model	Size	RMS/Peak Power
XD-1544	15"	700W/1400W
XD-1244	12"	500W/1000W
XD-1044	10"	450W/900W
XD-844	8"	300W/600W
XD-6.5	6.5"	150W/300W



DX Series Subwoofers

- SVC 4-ohm Impedance • Stamped Basket • 2" High-Temp Voice Coil

Model	Size	RMS/Peak Power
DX-154	15"	500W/1000W
DX-124	12"	400W/600W
DX-104	10"	300W/600W





SQ Series Full Range



- Woven Carbon Fiber Cone • Butyl Rubber Surround • Ferro Fluid Cooled • 4-ohm Impedance

Model	Size	RMS/Peak Power	Voice Coil	Magnet
SQ-6.9	6 x 9"	80W/200W	1" Hi-Temp	25 oz.
SQ-5.7	5 x 7"	75W/150W	-	20 oz.
SQ-6.5	6.5"	80W/160W	-	20 oz.
SQ-5.25	5.25"	60W/120W	1" Hi-Temp	-
SQ-4.6	4 x 6"	50W/100W	1" Hi-Temp	-
SQ-4.0	4"	45W/90W	1" Hi-Temp	10 oz.
SQ-3.5	3.5"	40W/80W	1" Hi-Temp	10 oz.

SQ Tweeters

SQ-T2

- Teteron Dome Tweeters
- 2-Way Passive Crossover
- Ferro Fluid Cooling • Flush Swivel/Surface/Angle Mount
- 60 Watt RMS/120 Watt Max • 4-ohm Impedance
- High-Density Neodymium Magnet



SQ-T12

- 1" Tweeters • Niobium Micro Dome Tweeters
- Polypropylene Diaphragm
- Built-in Crossover • Surface Flush Mount • 50 Watt RMS/100 Watt Max
- 4-ohms Impedance



Amplifier Kits

AB-AK1/0 - 0-Gauge Amp Kit

- 17ft 0 Gauge Red Power Cable
- 3ft 0 Gauge Black Power Cable
- 17ft 18 Gauge Blue Turn-on Wire
- 25ft 12 Gauge Speaker Wire
- 17ft Deluxe RCA Interconnect
- Two 0-Gauge Ring Terminal
- 10 Wire Ties
- 3 Screws
- Deluxe High Quality Fuse Holder
- Gold Plated ANL Fuse(250A)

- AK-5 AWG MINI - 4-Gauge Amp Kit**
- AK-8 AWG MINI - 8-Gauge Amp Kit**



Sound Processors

AB-7B-V

- High End 7-Band Equalizer Voltage Display • Frequency Steps: 50Hz, 125Hz, 315Hz, 750Hz, 2.2KHz, 6KHz, 12KHz
- 7V Preamp Output • 2-RCA Inputs • Fader Control • Sub Frequency and Volume Control • Dim: 9" L x 8" W x 2" H



ABX-3.1A

- Front and Rear Hi-Pass • Subwoofer Low Pass • Input Impedance: 20K-ohms • Output Impedance: Less than 150-ohm • 8V Peak Outputs Level • Channel Separation
- Subsonic Filter • Low Pass/High Pass





Marine Series Amplifiers



- Hi-Pass Filter • Low Pass Filter • Subsonic Filter • Bass Boost • 1-ohm (MR-2500.1) • 2-ohm Stereo (MR-160.4)

Model	Chs/Class	1 ohm	2 ohm	Max Power
MR-2500.1	1/-	2500W	-	2500W
MR-160.4	4/-AB	-	150W x 4	-

Marine Series Speakers



- Full Range Coaxial Components • 4mm Top Plate • 4-ohm Impedance

Model	Size	RMS/Max Power	Voice Coil	Magnet
AB-MRE 6.9	6 x 9"	150W/300W	1" EISV	15 oz.
AB-MRE 7	7"	- /200W	1" EISV	15 oz.
AB-MRE 6.5F	6.5"	- /200W	1" EISV	10 oz.

Marine Subwoofer



- 10" Subwoofer • Voice Coil 2" EISV-Copper Wire • 750 Watts Max Power • 4-ohm Impedance • 35-1k Hz Frequency Response • Top Plate 8mm • Magnet 70 oz.

VFL Series Amplifiers



- Low Level Input and Output • Variable Low Pass Filter

Model	Chs/Class	4 ohm RMS	2 ohm RMS	Max Power
VFL-150.1	1/D	-	-	2900W RMS
VFL-350.4	4/AB	175W x 4	250W x 4	2500W
VFL-100.1	1/D	-	-	1500W RMS

VFL Pro Speakers



- Paper Cone • Accordion Surround or Foam Surround • 8-ohm Impedance

Model	Size	RMS/Peak Power	Voice Coil	Magnet
VFL-10MR-8	10"	250W/500W	-	40 oz.
VFL-65MR	6.5"	175W/150W	1.5" Hi-Temp	20 oz.
VFL-69MR	6 x 9"	175W/350W	1.5" Hi-Temp	20 oz.

- Territory Restrictions -