

KORE (R)

Class AB Amplifiers

- Full Mosfet Circuitry
- Stainless Steel Finish Heat Sink
- 0-18dB Variable Bass Boost
- Thermal, Short & Overload Protection Circuitry
- Variable High Pass and Low Pass Filters
- Double Sided Black Epoxy
- Quiet Fan Cooling System



Model	Channels	4 ohm RMS	2 ohm RMS	1 ohm RMS	2 ohm RMS Mono
HK1998	– 1	500Wx1	600Wx1	1200Wx1	-
HK1398	– 2	400Wx2	600Wx2	600Wx2	1600Wx1
HK898	– 2	300Wx2	400Wx2	600Wx2	1200Wx1
HK798	– 2	200Wx2	300Wx2	400Wx2	800Wx1
HK598	– 4	200Wx4	400Wx4	800Wx4	-
HK398	– 2	150Wx2	200Wx2	300Wx2	600Wx1

Class X Mono Amplifiers

Model	Channels	4 ohm RMS	2 ohm RMS	1 ohm RMS
HK1000D	– 1	500Wx1 (17V DC)	800Wx1 (17V DC)	1000Wx1 (17V DC)
HK2000D	– 1	1000Wx1 (17V DC)	1500Wx1 (17V DC)	1800Wx1 (17V DC)
HK4000D	– 1	2500Wx1 (17V DC)	4000Wx1 (17V DC)	-
HK10KA	– 1	3500Wx1 (17V DC)	6000Wx1 (17V DC)	10000Wx1 (17V DC)

XE Series Amplifiers

- Full Mosfet Circuitry
- Variable High/Low Pass Cross-Over 50 250Hz
- Variable Bass Boost 0-18dB @ 45Hz
- 3-Way Protection Circuitry • Low Level Output
- 2 ohm Stereo Stable • High/Low Level Inputs



Model	Channels	4 ohm RMS	2 ohm RMS	4 ohm Bridged Max
M300XE	– 2	125Wx2	250Wx2	500Wx1
M500XE	– 4	125Wx4	225Wx4	500Wx2
M600XE	– 2	175Wx2	350Wx2	700Wx1
M700XE	– 2	250Wx2	500Wx2	1000Wx1
M1900XE	– Mono	500Wx1	1000Wx1 Max	-

XL Series Subwoofers

- Patented Die-Cast Black Basket
- Reinforced Ribbed High Foam Surround
- Hi-Temp Kapton Voice Coil Structure



Model	Size	Max Power	Ohms	Magnet Weight
MA1808XL	– 18"	1600W	Dual 4 ohm	350 oz.
MA1508XL	– 15"	1200W	Dual 4 ohm	260 oz.
MA1208XL	– 12"	1200W	Dual 4 ohm	240 oz.
MA1008XL	– 10"	1000W	Dual 4 ohm	240 oz.
MA808XL	– 8"	800W	Dual 4 ohm	200 oz.

XE Series Subwoofers

- Reinforced Ribbed High Foam Surround
- Black Powder Coated Stamped Steel Basket
- Copper Wound Voice Coils



Model	Size	Max Power	Ohms	Magnet Weight
MA183XE	– 18"	1100W	Dual 4 ohm	200 oz.
MA153XE	– 15"	900W	Dual 4 ohm	150 oz.
MA123XE	– 12"	700W	Dual 4 ohm	150 oz.
MA103XE	– 10"	600W	Dual 4 ohm	110 oz.
MA83XE	– 8"	500W	Dual 4 ohm	80 oz.

XQ Series Subwoofers

- High Profile Triple Treated Surround
- Black Powder Coated Stamped Steel Basket
- Platinum Plated Block Terminals



Model	Size	Max Power	Ohms	Magnet Weight
MA115XQ	– 15"	900W	DVC 4 + 4ohm	80 oz.
MA112XQ	– 12"	600W	DVC 4 + 4ohm	60 oz.
MA110XQ	– 10"	500W	DVC 4 + 4ohm	50 oz.
MA8XQ	– 8"	400W	DVC 4 + 4ohm	

HK Full Range



Common Features:

- Kapton Voice Coil for Highest Power Handling
- Strontium Magnet for Optimum Performance
- 25mm 360° Swivel Mount PEI Tweeter
- Mica Cone for Clean Sound Reproduction

Model	Size	Type	Max. Power Handling
HK69	– 6 x 9"	3-Way	300Watts
HK68	– 6 x 8"/5 x 7"	2-Way	200Watts
HK65	– 6.5"	2-Way	200Watts
HK52	– 5.25"	2-Way	140Watts
HK46	– 4 x 6"	2-Way	120Watts
HK40	– 4"	2-Way	120Watts
HK35	– 3.5"	2-Way	80Watts

HK Component System



Common Features:

- Kapton Voice Coil
- Balanced 12dB Crossover
- 2-Layer High Temp Voice Coil
- PEI Titanium Tweeter
- Mica Cone

Model	Size	Type	Max. Power Handling
HK57C	– 5 x 7"/6 x 8"	Comp System	250Watts
HK60C	– 6.5"	Comp System	200Watts
HK50C	– 5.25"	Comp System	160Watts