



## "V" Series Multi-Channel & Mono Amps



- Full Range Class A/B Volt Series Amplifiers • Bass Boost • Hi/Low Pass Filter
- High Input with Floating Ground • Advanced Protection

| Model    | Channels | 4Ω RMS        | 2Ω RMS        | Bridged @ 4Ω  | Max Power  |
|----------|----------|---------------|---------------|---------------|------------|
| V 500.2  | 2        | 125 Watts x 2 | 250 Watts x 2 | 500 Watts x 1 | 500 Watts  |
| V 1000.4 | 4        | 125 Watts x 4 | 250 Watts x 4 | 500 Watts x 2 | 1000 Watts |
| V 1000.1 | 1        | -             | 500 Watts x 1 | 250 Watts x 1 | 1000 Watts |

## "V" Series Subwoofers

- Powder Coated Stamped Solid Steel Basket • Poly-glass Fiber Caped UV Treated Paper Cone • Dual Wave Roll Surrounds • Dual 4" and 2" CCAW Voice Coils on an Aluminum Former with Reinforced Neck Joints • High Ferrite Stacked Magnets • 5-Way Binding Posts with Push or Banana Nickel Plated Terminals



| Model    | Size | Power RMS/Peak | Impedance  | Magnet |
|----------|------|----------------|------------|--------|
| REBEL 10 | 10"  | 500W/1000W     | Dual 4 ohm | 65 oz. |
| REBEL 12 | 12"  | 500W/1000W     | Dual 4 ohm | 65 oz. |
| REBEL 15 | 15"  | 500W/1000W     | Dual 4 ohm | 65 oz. |



## Nano Block Series A/B Class Amplifiers

- Full Range Amplifier with MOSFET Power Supply • Heavy Duty Aluminum Alloy Heatsink
- Adjustable High/Low Pass Filters • 3-Way Protection Circuitry • Subsonic Filter • Chrome-plated RCA Level Inputs and Screw Terminals



| Model | Channels | 4Ω<br>RMS | 2Ω<br>RMS | Bridged @<br>4Ω | Max<br>Power | Bass<br>Knob |
|-------|----------|-----------|-----------|-----------------|--------------|--------------|
| NX2   | 2        | 120W x 2  | 240W x 2  | 240W x 1        | 480W         | No           |
| NX4   | 4        | 100W x 4  | 200W x 4  | 400W x 2        | 1600W        | No           |
| NX5   | 5        | 120W x 4  | 240W x 4  | 480W x 2        | 1600W        | Optional     |

## Nano Block Series D Class Amplifiers

- MOSFET Power Supply • Heavy Duty Aluminum Alloy Heatsink • Subsonic Filter • Adjustable Low Pass Filter • Selectable Bass Boost • 3-Way Protection Circuitry • Chrome-plated RCA Level Inputs and Screw Terminals • NE End Caps are Optional



| Model | Channels | 4Ω<br>RMS | 2Ω<br>RMS | 1Ω<br>RMS | Max<br>Power | Bass<br>Knob |
|-------|----------|-----------|-----------|-----------|--------------|--------------|
| N2    | 1        | 200W x 1  | 400W x 1  | 800W x 1  | 1600W        | Optional     |
| N3    | 1        | 450W x 1  | 700W x 1  | 1400W x 1 | 2800W        | Optional     |
| N4    | 1        | 650W x 1  | 1000W x 1 | 2000W x 1 | 4000W        | Optional     |

## D Block Series Amplifiers

- MOSFET Power Supply • Brushed Aluminum "Finless" Heat Sink • Adjustable Low/High Pass Filter • Adjustable Parametric Bass EQ • 6-Way Protection Circuitry • Nickel-plated Connectors



| Model | Channels | 4Ω<br>RMS | 2Ω<br>RMS | 1Ω<br>RMS | Max<br>Power | Bass<br>Knob |
|-------|----------|-----------|-----------|-----------|--------------|--------------|
| D1200 | 1        | 225W x 1  | 450W x 1  | 600W x 1  | 1200W        | Optional     |
| D2400 | 1        | 325W x 1  | 650W x 1  | 1200W x 1 | 2400W        | Optional     |
| D3600 | 1        | 475W x 1  | 950W x 1  | 1800W x 1 | 3600W        | Optional     |

## Master Mind Series Full Range Amplifiers

- Full Range Amplifier with MOSFET Power Supply • Heavy Duty Aluminum Alloy Heatsink • Adjustable High/Low Pass Filters • 3-Way Protection Circuitry
- Subsonic Filter • Chrome-plated RCA Level Inputs and Screw Terminals



| Model | Channels | 4Ω<br>RMS | 2Ω<br>RMS | Bridged @<br>4Ω | Max<br>Power | Bass<br>Knob |
|-------|----------|-----------|-----------|-----------------|--------------|--------------|
| M42   | 2        | 120W x 2  | 240W x 2  | 240W x 1        | 480W         | No           |
| M84   | 4        | 100W x 4  | 200W x 4  | 400W x 2        | 1600W        | No           |
| NX5   | 5        | 120W x 4  | 240W x 4  | 480W x 2        | 1600W        | Optional     |

## Bass Gain Remote Control

DBR – For all Massive Mono Block Amplifiers





## V Series Subwoofers

- Stamp Steel Basket • Polymica Cone with Woven Glass Fiber Dust Cap • 1.5" Four Layer Voice Coil with Aluminum Former and Reinforce Neck Joint • 1" N-Roll Polyester Foam Surround

| Model | Size | Power RMS/Peak | Impedance  | Magnet |
|-------|------|----------------|------------|--------|
| V10   | 10"  | 250W/500W      | Dual 4 ohm | 40 oz. |
| V12   | 12"  | 250W/500W      | Dual 4 ohm | 40 oz. |
| V122  | 12"  | 250W/500W      | Dual 2 ohm | 40 oz. |



## TW Series Subwoofers

- Stamp Steel Basket • Finger "V" Ultra Light Cone • 2.5" Voice Coil • 1" Tall Santoprene Surround • Woven Silver Plated Tinsel Leads • Push-In or Banana for 8 AWG Terminals

| Model | Size | Power RMS/Peak | Impedance  | Magnet |
|-------|------|----------------|------------|--------|
| TW10  | 10"  | 500W/1000W     | Dual 4 ohm | 80 oz. |
| TW12  | 12"  | 500W/1000W     | Dual 4 ohm | 80 oz. |
| TW15  | 15"  | 500W/1000W     | Dual 4 ohm | 80 oz. |



## DC Series Subwoofers

- Aluminum Die-Cast Basket • Finger "V" Ultra Light Cone • 2.5" Voice Coil • 1" Tall Santoprene Surround • Woven Silver Plated Tinsel Leads • Push-In or Banana Nickel Plated Terminals

| Model | Size | Power RMS/Peak | Impedance  | Magnet  |
|-------|------|----------------|------------|---------|
| DC10  | 10"  | 600W/1200W     | Dual 4 ohm | 120 oz. |
| DC12  | 12"  | 600W/1200W     | Dual 4 ohm | 120 oz. |





## V Series Coaxial Speakers

- Heavy Gauge Steel/Low Resonance Composite Baskets • UV Protected Poly Injected Cones • Copper Voice Coils • Butyl Rubber Surrounds • Fully Isolated Tinsel Leads • Custom 2-Piece Paintable Grills

| Model | Size             | Power RMS/Peak | Impedance | Tweeter           |
|-------|------------------|----------------|-----------|-------------------|
| VX5   | 5.25", 2-Way     | 50W/200W       | 4 ohm     | 20mm Silk Dome    |
| VX6   | 6.5", 2-Way      | 60W/250W       | 4 ohm     | 20mm Silk Dome    |
| VX68  | 5x7"/6x8", 2-Way | 60W/250W       | 4 ohm     | 20mm Silk Dome    |
| VX69  | 6x9", 3-Way      | 70W/300W       | 4 ohm     | 2" Mid/13mm Mylar |



## V Series Component Speakers (2-Way)

VK6

- 6.5" 4 ohm Speaker • Heavy Gauge Steel/Low Resonance Composite Baskets • UV Protected Polymica Injected Cones • Copper Voice Coils • Butyl Rubber Surrounds • Handle 60-250 Watts • 12 Db Crossovers • 20mm Silk Soft Dome Swivel Tweeters • Fully Isolated Tinsel Leads • Custom 2-Piece Paintable Grills



## Slim Series Component Speakers

- SLIM SERIES Stage II Component Speakers • Compact Size • Steel Basket • Polymica Cone • Shallow Mounting • 12 Db External Crossover • 20mm Silk Soft Dome Tweeter

| Model | Size         | Power RMS/Peak | Impedance |
|-------|--------------|----------------|-----------|
| SK5II | 5.25", 2-Way | 90W/210W       | 4 ohm     |
| SK6II | 6.5", 2-Way  | 100W/220W      | 4 ohm     |



## Components/ Convertibles Speakers

- Cast Basket • Carbon Fiber Cones • 28mm Silk Dome Tweeter • 18 Db External Crossover

| Model    | Size        | Power RMS/Peak | Impedance |
|----------|-------------|----------------|-----------|
| CK6III   | 6.5", 2-Way | 130W/280W      | 4 ohm     |
| CK6.9III | 6x9", 2-Way | 150W/320W      | 4 ohm     |



## Tweeter

CT1A

- 25mm 4Ω Aluminum Dome Tweeter • 12 dB Crossovers • 60W RMS/120W Peak • Neodymium Magnets • Flexible Mounting Options including Surface or Flush Mount



