



LESCO

D I S T R I B U T I N G



PrecisionPower
Absolutely State of the Art Mobile Audio

Amplifiers & Subwoofers

Power Class A/B Series Amplifiers



- Common Features:**
- Large TO218 MOSFET Transistors • Sequenced Delays Eliminate Residual Power-Up/Power-Down Pops • Full Signal Path Low Noise/ Distortion Circuitry Topology • Triple Darlington Audio Output Stages
 - Extra Low Current Drive Stage Increases Efficiency and Sound Clarity
 - Removeable Power and Thermal Connection • Close Tolerance Signal Path Components - 1% Resistors & 5% Capacitors

Model	Channels	4 ohm RMS	2 ohm RMS	4 ohm RMS Bridged	Bass Knob
PC360.2	2	102W x 2	180W x 2	360W x 1	Yes
PC650.2	2	195W x 2	325W x 2	650W x 1	Yes
PC400.4	4	70W x 4	100W x 4	200W x 2	-
PC640.4	4	115W x 4	160W x 4	320W x 2	-
PC740.5	5	60W x 4/250 x 1	90W x 4/380 x 1	180W x 2	Yes

Class D Series

Model	Channels	4 ohm RMS	2 ohm RMS	4 ohm RMS Bridged	Bass Knob
PC1000.1	1	-	1000W x 1	-	Yes

Power Class Subwoofer Series



- Common Features:**
- Die-Cast Aluminum Frame w/Candy Apple Finish • Non Pressed Paper Pulp Cone • Polyether Foam Surround • Cast Aluminum Heat-Sink Dust-Cap • 2.5" 4-layer Voice Coil on Anodized Aluminum Former • Strontium Ferrite Magnet • Nickel Plated 8ga. Compression Wire Terminals

Model	Size	RMS Power	Voice Coil Configuration	Magnet
PC.12	12"	800 Watts	2.5" Dual 2 ohm	170 oz.
PC.15	15"	900 Watts	2.5" Dual 2 ohm	170 oz.

Power Class D Subwoofer Series



- Common Features:**
- Power Class Dual Suspension • Pressed Paper Cone • Reinforced Foam Surround • 4 Layer Voice Coil • EVA Gasket • Aluminum Basket, Phase Plug, Pole Piece, T-Yoke for Efficient Heatsink Cooling • Aluminum VC Former • Compression Terminals

Model	Size	RMS Power	Voice Coil Configuration	Magnet
PC.15DS	15"	1200 Watts	3" Dual 4 ohm	-
PC.18DS	18"	1600 Watts	4" Dual 4 ohm	-

Authorized Dealers Only
– Call your Sales-Rep for Details –
– Territory Restrictions –



LESCO

D I S T R I B U T I N G



PrecisionPower®
Absolutely State of the Art Mobile Audio

Amplifiers & Subwoofers

Sedona Class A/B Series Amplifiers



- Common Features:**
- Mosfet Power Supply • Variable High, Low and Subsonic Crossovers
 - Variable Bass Boost • High/Low Level Input • Brushed Aluminum Finish

Model	Channels	4 ohm RMS	2 ohm RMS	4 ohm RMS Bridged	Bass Knob
S200.2	2	70W x 2	100W x 2	200W x 1	-
S420.2	2	130W x 2	210W x 2	420W x 1	-
S580.2	2	190W x 2	290W x 2	580W x 1	-
S320.4	4	55W x 4	80W x 4	160W x 2	-
S580.4	4	100W x 4	145W x 4	290W x 2	-
S760.4	4	120W x 4	190W x 4	380W x 2	-
S580.5	5	55W x 4/160 x 1	80W x 4/260 x 1	160W x 2	-
S270.1	1	170W x 1	270W x 1	-	-

Class D Series

Model	Channels	4 ohm RMS	2 ohm RMS	1 ohm RMS	Bass Knob
S550.1D	1	240W x 1	400W x 1	550W x 1	-
S850.1D	1	350W x 1	600W x 1	850W x 1	-
S1300.1D	1	520W x 1	900W x 1	1300W x 1	-
S2000.1D	1	750W x 1	1300W x 1	2000W x 1	-

Sedona Subwoofer Series



- Common Features:**
- Injection-Molded Polypropylene/Mica Cone and Dust Cap • ABS Gasket
 - Butyl Rubber Surround • 4 Layer Voice coil • Kapton VC Former • Vented Pole Piece • Stitched Tinsel Leads • Conex Composite Spider

Model	Size	RMS Power	Voice Coil Configuration	Magnet
S.12	12"	250 Watts	2" Dual 4 ohm	-
S.15	15"	300 Watts	2" Dual 4 ohm	-

Authorized Dealers Only
 – Call your Sales-Rep for Details –
 – Territory Restrictions –



LESCO

D I S T R I B U T I N G

PrecisionPower®
Absolutely State of the Art Mobile Audio

Pro Audio Full Range Speaker Series

Model	Size & Type	Peak Power	Impedance
PT.2	Bullet Tweeter (Pair)	90 Watts	3 ohm
T.2	1" Tweeter (Pair)	100 Watts	4 ohm
PT.5	Horn Tweeter	100 Watts	4 ohm
PM.65	6.5" Mid Range	100 Watts	3 ohm
PM.65NEO	6.5" Mid Range	120 Watts	3 ohm
PM.8	8" Mid Range	200 Watts	3 ohm
PM.10	10" Mid Range	350 Watts	3 ohm



Sedona Full Range Speaker Series

Common Features:
 • Stamped Steel Basket • Carbon Injection Cone • Mylar Midrange and Tweeter • Butyl-Rubber Surround • 1" Aluminum Coil Former

Model	Size	RMS Power	Impedance	Mid Size	Tweeter
S.693	6 x 9"	80 Watts	4 ohm	2"	1/2"
S.653	6 x 5"	60 Watts	4 ohm	1/2"	Piezo
S.573	5 x 7"	60 Watts	4 ohm	1/2"	Piezo
S.52	5.25"	50 Watts	4 ohm	-	1/2"
S.42	4"	40 Watts	4 ohm	-	1/2"



Sedona Components

• 6.5" Mid-Bass • Polypropylene Cone • Butyl Rubber Surround
 • Zolon Coated Low Resonance Basket • 1" Aluminum Voice Coil
 • Mylar Dome Tweeter • Rubber Magnet Cover

Model	Power Handling	Impedance	Voice Coil	Ferrite Magnet
S2.65C	100 Watts	4 ohm	1"	20 oz.



Authorized Dealers Only
 – Call your Sales-Rep for Details –
 – Territory Restrictions –



LESCO

D I S T R I B U T I N G



PrecisionPower
Absolutely State of the Art Mobile Audio

Power Class Full Range Speaker Series

Common Features:

- Low Resonance Composite Basket • Bi-Ampable Operation • 1" Kapton Coil Former • UV Coated Paper Cone • 1" Swivel Silk Dome Tweeter
- Butyl Rubber Surround • CONEX Spider Suspension • Passive Cross-overs Included

Model	Size	RMS Power	Impedance
PC.692	6 x 9"	150 Watts	4 ohm
PC.652	6.5"	120 Watts	4 ohm
PC.52	5.25"	100 Watts	4 ohm
PC.572	5 x 7"	120 Watts	4 ohm



Power Class Components

6.5" Midbass

- Kevlar Reinforced Paper Cone w/Laminated Foam Backing • Butyl Rubber Surround • Low Resonance Polyphenylene Sulfide Basket • CCAW 2" Voice Coil • Glass Fiber VC Former • High Strength Neodymium Motor

2.5" Midrange

- Aluminum Cone • Butyl Rubber Surround • Low Resonance Polyphenylene Sulfide Basket • Aluminum Dust Cap • CCAW 1" Voice Coil • Aluminum VC Former with Cooling Vents • High Strength Neodymium Motor

20mm Tweeter

- Inverted and Dimpled Aluminum Diaphragm • CCAW 20mm Voice Coil
- Kapton VC Former • High Strength Neodymium Motor

Model	Size	Power Handling	Impedance	Mid Range	Tweeter
PC2.65C	6.5" Mid-Bass	90 Watts	3 ohm	-	20mm
PC3.65C	6.5" Mid-Bass	100 Watts	3 ohm	2.5"	20mm



Authorized Dealers Only
– Call your Sales-Rep for Details –
– Territory Restrictions –