

## Full Range Amplifiers A/B Class

- Mosfet Power Supply • Variable High & Low-Pass Crossovers
- Variable Bass Boost • Variable Gain Control • Stable at 2Ω



Model	Channels	Power	Peak
<b>ASA1100.5</b>	4+1	150Watts x 4 + 500Watts x 1	2200 Watts
<b>ASA700.5</b>	4+1	100Watts x 4 + 400Watts x 1	1400 Watts
<b>ASA600.4</b>	4	200Watts x 4	1600 Watts
<b>ASA400.4</b>	4	100Watts x 4	800 Watts
<b>ASA800.2</b>	2	400Watts x 2	1600 Watts
<b>ASA600.2</b>	2	300Watts x 2	1200 Watts
<b>ASA400.2</b>	2	200Watts x 2	800 Watts
<b>ASA300.2</b>	2	150Watts x 2	600 Watts
<b>ASA200.2</b>	2	100Watts x 2	400 Watts
<b>ASA-BASS</b>	-	Optional Remote Bass Knob	

## Mono-Block Amplifiers

- Variable Low-Pass Crossover • Variable Subsonic Filter
- Variable Bass Boost • Remote Gain Included • 1Ω Stable



Model	Channels	Power	Peak
<b>ASA2200.1D</b>	1	2200Watts x 1	4000 Watts
<b>ASA1500.1D</b>	1	1500Watts x 1	3000 Watts
<b>ASA1000.1D</b>	1	1000Watts x 1	2000 Watts

## Mono-Block Amplifiers A/B Class

- Variable Low-Pass Crossover • 2Ω Stable
- Variable Bass Boost • Remote Gain Included



Model	Channels	Power	Peak
<b>ASA600.1</b>	1	600Watts x 1	1200 Watts
<b>ASA400.1</b>	1	400Watts x 1	800 Watts

### S Series Subwoofer

- Black Powder Coated Steel Basket • 2" ASV Voice Coil Formers
- Large Roll, Santoprene Surrounds • Pole and Aero Vented Cooling



Model	Size	Power Handling RMS/Peak	Frequency Response	Motor	Impedance
<b>S-12D</b>	– 12"	300W/600W	29Hz-450Hz	124 oz.	Dual 4Ω
<b>S-12</b>	– 12"	300W/600W	33Hz-450Hz	124 oz.	Single 4Ω
<b>S-10D</b>	– 10"	275W/550W	33Hz-500Hz	116 oz.	Dual 4Ω
<b>S-682</b>	– 10"	275W/550W	33Hz-500Hz	116 oz.	Single 4Ω

### L Series Subwoofer

- Custom CNC Cut, Cast Aluminum Basket • Large Roll, Santoprene Surrounds • Proprietary 4-Layer, Non-Pressed Paper, DDC Finish Cone
- Large Motor Structures for High Power Handling



Model	Size	Power Handling RMS/Peak	Frequency Response	Motor	Impedance
<b>L-15D</b>	– 15"	500W/1000W	20Hz-400Hz	220 oz.	Dual 4Ω
<b>L-12D</b>	– 12"	400W/800W	24Hz-450Hz	149 oz.	Dual 4Ω
<b>L-10D</b>	– 10"	350W/700W	32Hz-500Hz	140 oz.	Dual 4Ω

### S Series Full Range Co-ax Speakers & Components

- Black 2-Layer Paper, DDC Cone, Low Profile Pure Silk Dome Tweeter
- Double Pressed Treated Foam Surround • OEM Drop in Replacement
- Multiple Sixes include Hard-to-Find Speakers



Model	Description	RMS/Peak
<b>S-6C</b>	Component 6.5" w/Crossover, Pure Silk Dome Tweeter	70W/210W
<b>S-5C</b>	Component 5.25" w/Crossover, Pure Silk Dome Tweeter	50W/150W
<b>S-693</b>	6 x 9"	70W/210W
<b>S-682</b>	6 x 8"	60W/180W
<b>S-412</b>	4 x 4"	50W/150W
<b>S-675</b>	6.75"	50W/150W
<b>S-652</b>	6.5"	50W/150W
<b>S-65T</b>	6.5"	45W/135W
<b>S-522</b>	5.25"	40W/120W
<b>S-462</b>	4 X 6"	35W/105W
<b>S-402</b>	4"	35W/105W
<b>S-352</b>	3.5"	30W/90W