



Cozmik Series Subwoofers

- 2.5" Diameter High Temperature 4 Layer Voice Coil • Layered UV Treated Foam Surround • Orange Anti-Resonance Heavy Gauge Basket • Custom Tooled Magnet Boot with Intergrated Direct Connect Speaker Terminals
- Poly-Injected Cone with Orange Iridescent Ring



| Model | Structure | Max Power | RMS Power |
|-----------------|-------------------------|-----------|-----------|
| QCSW10D2 | – 10" Dual 2Ω Subwoofer | 1500Watts | 750Watts |
| QCSW10D4 | – 10" Dual 4Ω Subwoofer | 1500Watts | 750Watts |
| QCSW12D2 | – 12" Dual 2Ω Subwoofer | 1500Watts | 750Watts |
| QCSW12D4 | – 12" Dual 4Ω Subwoofer | 1500Watts | 750Watts |
| QCSW15D2 | – 15" Dual 2Ω Subwoofer | 2000Watts | 1000Watts |
| QCSW15D4 | – 15" Dual 4Ω Subwoofer | 2000Watts | 1000Watts |

"Q" Series Subwoofers

- 2" Diameter High Temperature Kapton 4 Layer Voice Coil • Multi-Layered Treated Paper Cone • Layered UV Treated Foam Surround • Orange Anti-Resonance Heavy Gauge Basket • Gold Plated Push Terminals • Custom Tooled Magnet Boot with Pole Piece Ventilation



| Model | Structure | Max Power | RMS Power |
|----------------|---------------------------|-----------|-----------|
| QPW10S4 | – 10" Single 4Ω Subwoofer | 800Watts | 400Watts |
| QPW10D4 | – 10" Dual 4Ω Subwoofer | 800Watts | 400Watts |
| QPW12S4 | – 12" Single 4Ω Subwoofer | 800Watts | 400Watts |
| QPW12D4 | – 12" Dual 4Ω Subwoofer | 800Watts | 400Watts |

Solar Series Amplifiers

- Audiophile Grade Components • Qsink Technology (Heat Management System) • Enhanced Dynamic Performance • Hi-Efficiency Mosfet Outputs
- On-Board (Fully Variable) High/LowPass Crossver (QSA2150, QSA4150)
- On-Board (Fully Variable) Low Pass X-Over



| Model | Internal Circuitry | 4Ω @ 14.4v | 2Ω @ 14.4v |
|-----------------|--------------------|-------------------|------------|
| QSA2150 | – Class AB | 2 x 150W/1 x 600W | 2 x 300W |
| QSA4150 | – Class AB | 4 x 150W/2 x 600W | 4 x 300W |
| QSA1000D | – Class AB | 1 x 500W | 1 x 1000W |
| QSA1500D | – Class AB | 1 x 750W | 1 x 1500W |



"Q" Series Amplifiers

- Audiophile Grade Components • Qsink Technology (Heat Management System) • Enhanced Dynamic Performance • Hi-Efficiency Mosfet Outputs
- On-Board (Fully Variable) High/Low Pass X-Over • Bass Remote Control



| Model | Internal Circuitry | 4Ω @ 14.4v | 2Ω @ 14.4v | 1Ω @ 14.4v |
|----------------|--------------------|--------------------|------------|------------|
| QA2160 | – Class AB | 2 x 160W/1 x 640W | 2 x 320W | – |
| QA4160 | – Class AB | 4 x 160W/2 x 640W | 4 x 320W | – |
| QA2260 | – Class AB | 2 x 260W/1 x 1040W | 2 x 520W | – |
| QA4260 | – Class AB | 4 x 260W/2 x 1040W | 4 x 520W | – |
| QA1800D | – Class AB | – | 1 x 1200W | 1 X 1800W |

Cozmik Series Coaxial Speakers

- 4Ω Nominal Impedance • Polypropylene Cone • Rubber Butyl Surround
- Custom Tooled Magnet Boot • .75" PEI Dome with Chrome Tweeter Flange
- Orange Heavy Gauge Basket



Silk Mounting Tweeter

- Built-in X-Over • Neodymium Magnet • Tri-Mode Mounting Positions

| Model | Structure | Max Power | RMS Power | Magnet Wt. |
|--------------|--------------------------|-----------|-----------|------------|
| QC1ST | – 1" Mounting Tweeter | 150Watts | 75Watts | 10 oz. |
| QC460 | – 4 x 6" Coaxial Speaker | 150Watts | 75Watts | 10 oz. |
| QC525 | – 5.2" Coaxial Speaker | 180Watts | 60Watts | 15 oz. |
| QC570 | – 5 x 7" Coaxial Speaker | 180Watts | 60Watts | 15 oz. |
| QC650 | – 6.5" Coaxial Speaker | 180Watts | 60Watts | 15 oz. |
| QC690 | – 6 x 9" Coaxial Speaker | 210Watts | 70Watts | 25 oz. |

Cozmik Series Components



| Model | Structure | Max Power | RMS Power | Magnet Wt. |
|---------------|--------------------------|-----------|-----------|------------|
| QC500C | – 5.2" Component Speaker | 180Watts | 60Watts | 15 oz. |
| QC600C | – 6.5" Component Speaker | 180Watts | 60Watts | 15 oz. |



Solar Series Subwoofers

- 2" Kapton Voice Coil • Layered UV Treated Foam Surround • Iridescent Orange Anti-Resonance Heavy Gauge Basket • Polypropylene Cone • Custom Tooled Protective Magnet Boot • Fully Isolated High Excursion Tinsel Leads



| Model | Structure | Max Power | RMS Power |
|---------------|---------------------------|-----------|-----------|
| QS10S4 | - 10" Single 4Ω Subwoofer | 500Watts | 250Watts |
| QS10D4 | - 10" Dual 4Ω Subwoofer | 500Watts | 250Watts |
| QS12S4 | - 12" Single 4Ω Subwoofer | 500Watts | 250Watts |
| QS12D4 | - 12" Dual 4Ω Subwoofer | 500Watts | 250Watts |

Solar Series Coaxial Speakers

- Polypropylene Cone • RubberButyl Surround • Mylar Dome Tweeter • Neodymium Tweeter • Black Heavy Gauge Basket



| Model | Structure | Max Power | RMS Power | Magnet Wt. |
|---------------|--------------------------------|-----------|-----------|------------|
| QS1TW | - 1" Swivel Dome Tweeter | 150Watts | 35Watts | - |
| QS2TW | - 1" Directional Mount Tweeter | 150Watts | 35Watts | - |
| QS3500 | - 3.5" Coaxial Speaker | 60Watts | 15Watts | 8 oz. |
| QS4000 | - 4" Coaxial Speaker | 100Watts | 30Watts | 10 oz. |
| QS4600 | - 4 x 6" Coaxial Speaker | 100Watts | 30Watts | 10 oz. |
| QS5000 | - 5.25" Coaxial Speaker | 150Watts | 50Watts | 12 oz. |
| QS5700 | - 5 x 7" Coaxial Speaker | 150Watts | 50Watts | 15 oz. |
| QS6000 | - 6.5" Coaxial Speaker | 150Watts | 50Watts | 15 oz. |
| QS6003 | - 6.5" 3-Way Speaker | 175Watts | 60Watts | 15 oz. |
| QS6900 | - 6 x 9" 3-Way Speaker | 250Watts | 75Watts | 20 oz. |

Solar Component Speaker



| Model | Structure | Max Power | RMS Power | Magnet Wt. |
|---------------|--------------------------|-----------|-----------|------------|
| QS6500 | - 6.5" Component Speaker | 170Watts | 70Watts | 15 oz. |