



XTX Digital Amplifier Series

Common Features:

- High Speed Digital Amplifiers • Compact Design • Greater Dampening Factor for Lower, Tighter Bass • Higher Switching Frequencies for Lower Distortion



Mutli-Channel Amplifiers

Model	Channels/Class	4Ω RMS	2Ω RMS	Bridged @ 4Ω RMS
XTX800.4	4 – A/B	60W x 4	90W x 2	180W x 2
XTX500.5	4+1(Sub) – A/B	60W x 4 + 200W x 1	90W x 4 + 300W x 1	1800W x 2 + 300W x 1

Mutli-Channel Amplifiers

Model	Channels/Class	4Ω RMS	2Ω RMS	1Ω RMS Mono
XTX1500.1	Mono/D	190W x 1	330W x 1	500W x 1
XTX3000.1	Mono/D	600W x 1	1000W x 1	1400W x 1
XTX5000.1	Mono/D	1000W x 1	1700W x 1	2500W x 1
MT10K	Mono/D	5000W x 1	5900W x 1	7500W x 1

REX Subwoofer Series

Common Features:

- Pressed Steel Basket • Santoprene Rubber Surround • Mica Filled Poly Cone
- Foam Gasket • High Temperature 8-Layer Copper Voice Coil • Single Magnets
- FEA Optimized Motor Structure • Linear Conex Spiders

Model	Size	Impedance	Power Handling	Weight
REX 8	8"	Dual 4 ohm	175 Watts RMS	6.2 lbs.
REX 10	10"	Dual 4 ohm	175 Watts RMS	6.8 lbs.
REX 12	12"	Dual 4 ohm	175 Watts RMS	7.5 lbs.



SRX Subwoofer Series

Common Features:

- Pressed Steel Basket • Kraft Pulp Cone • Foam Gasket • Rubatek Foam Surround • 4-Layer Copper Voice Coil • Double Stack Magnets • FEA Optimized Motor Structure • Linear Spiders

Model	Size	Impedance	Power Handling	Weight
SRX 10	10"	Dual 2/4 ohm	300 Watts RMS	15.4 lbs.
SRX 12	12"	Dual 2/4 ohm	300 Watts RMS	16 lbs.
SRX 15	15"	Dual 2/4 ohm	300 Watts RMS	16.5 lbs.



SEX Subwoofer Series

Common Features:

- Cast Aluminum Basket • Dual Composite 2-Piece Cone • Wrap Around Rubber Gasket • Rugatek Foam Surround • 3" 4-Layer Aluminum Voice Coil • Triple Stack Magnets • Tork-Tite Terminal • FEA Optimized Motor Structure

Model	Size	Impedance	Power Handling	Weight
SEX 10	10"	Dual 2/4 ohm	600 Watts RMS	21 lbs.
SEX 12	12"	Dual 2/4 ohm	600 Watts RMS	21.5 lbs.
SEX 15	15"	Dual 2/4 ohm	600 Watts RMS	23.5 lbs.





SXX Subwoofer Series



- Common Features:**
- Cast Aluminum Basket • Dual Composite 2-Piece Cone • Rugatek Foam Surround
 - Wrap Around Rubber Gasket • 3" 8-Layer Aluminum Flat Wire Voice Coil • Triple Stack Magnets • Tork-Tite Terminal • FEA Optimized Motor Structure

Model	Size	Impedance	Power Handling	Weight
SXX 10	10"	Dual 2/4 ohm	1000 Watts RMS	24 lbs.
SXX 12	12"	Dual 2/4 ohm	1000 Watts RMS	24.5 lbs.
SXX 15	15"	Dual 2/4 ohm	1000 Watts RMS	27.6 lbs.
SXX 18	18"	Dual 2/4 ohm	1000 Watts RMS	-



XXX Subwoofer Series

- Common Features:**
- Cast Aluminum Basket • Dual Composite 2-Piece Cone • Rubber Surround
 - Integrated Gasket • 3" 4-Layer Aluminum Flat Wire Voice Coil • VMS Vented Magnet System • Tork-Tite Terminal • FEA Optimized Motor Structure

Model	Size	Impedance	Power Handling	Weight
SXX 12	12"	Dual 2/4 ohm	2000 Watts RMS	72 lbs.
SXX 15	15"	Dual 2/4 ohm	2000 Watts RMS	76 lbs.
SXX 18	18"	Dual 2/4 ohm	2000 Watts RMS	78 lbs.



Component Series

- Common Features:**
- FEA Optimized Motor Structure • 12dB/Octave Crossover Network • Tweeter Attenuation Control • 6.5" Midbass Driver • Rubber Surround • 1" Silk Dome Tweeter • Powerful Neodymium Motor • Swiveling Flush Mount

Model	Description	Power Handling
RE6.5C	6.5" Mica-filled Poly Cone/Pressed Steel Basket	50W RMS/100W Peak
XXX6.5C	6.5" Foamed Core Poly Cone/Cast Aluminum Basket	150W RMS/300W Peak



Full Range Coaxial Speakers

- Common Features:**
- Black Silk Polyester Diaphragm • Rubber Surround • 4 ohm Impedance

Model	Size	Configuration	Power Handling
RE5FR	5"	2-Way	75 Watts - 100 Watts
RE6.5FR	6.5"	2-Way	100 Watts - 125 Watts
RE5x7FR	5x7"	2-Way	100 Watts - 125 Watts
RE6x9FR	6x9"	3-Way	160 Watts - 200 Watts





TW-1 Tweeters

- 1" (25mm) Soft Dome Tweeters • Pure Copper Voice Coil Wire • Hexatech Aluminum Voice Coil Former • Neodymium Magnet • 45 Watts RMS Power Handling • Low-Viscosity Ferro-Fluid Cooling • 4 ohm Nominal Impedance



VLS-1 Digital Bass Processor

- Newly Designed • One-Band, Low Frequency, Quantum Digital Processor
- Wide and Sweep Adjustments • Bass Equalization Circuit • PFM Subsonic Filter Control • 1 Set of input/Output RCAs • Nickel Plated Contacts for Excellent Signal Transfer • Includes Wired Bass Remote

