



INFINITE 50A



Power Supply and Charger

- Operating voltage DC ----- 7,5V ~ 14,4V
- Operating voltage AC ----- 110V (93V ~ 140V) / 220V (163V ~ 240V)
- Impedance Output ----- 0 ~ 50A
- Consumption AC ----- 6,5A (127) ~ 4,6A (220V)
- Dimensions (H x W x D) mm ----- 64 x 185 x 172 mm
- Weight Kg ----- 1,5 Kg

Crossovers

9 Volts Outputs



MODEL

OUTPUTS

STX64	4	LOW (With Bass Boost) - MID LOW - MID HIGH - HIGH
STX104	5	LOW (With Bass Boost + Subsonic Filter) - MID LOW - MID HIGH - HIGH - FLAT
STX2448	4	DIGITAL CROSSOVER - EQUALIZER - LIMITER - DELAY - FREQUENCY GENERATOR

Audio Processor



EX Line

MODEL	# CHANNELS	RMS POWER at 14,4 V	RMS POWER at 12,6 V	FREQ RESP
EX 3000 EQ - 2OHM	1	3600w RMS 2Ω	3000w RMS 2Ω	10Hz to 25kHz
EX 5000 EQ - 1Ω	1	5600w RMS 1Ω	5000w RMS 1Ω	10Hz to 15kHz
EX 5000 EQ - 2Ω	1	5500w RMS 2Ω	5000w RMS 2Ω	10Hz to 15kHz
EX 8000 EQ - 1Ω	1	8900w RMS 1Ω	8000w RMS 1Ω	10Hz to 15kHz
EX 8000 EQ - 2Ω	1	8950w RMS 2Ω	8000w RMS 2Ω	10Hz to 15kHz
EX10500 EQ - 1Ω	1	11600w RMS 1Ω	10500w RMS 1Ω	10Hz to 15kHz
EX10500 EQ - 2Ω	1	11600w RMS 2Ω	10500w RMS 2Ω	10Hz to 15kHz
EX13500 EQ - 1Ω	1	14200w RMS 1Ω	13500w RMS 1Ω	10Hz to 10kHz