

LOUDSPEAKERS



TPT-MB10SLIM



TPT-MB8SLIM



TPT-MB6SLIM

400 Watts Continuous Power	300 Watts Continuous Power	200 Watts Continuous Power
200 Watts RMS Power	150 Watts RMS Power	100 Watts RMS Power
Impedance: 4 Ohms	Impedance: 4 Ohms	Impedance: 4 Ohms
Sensitivity: 95 dB	Sensitivity: 95 dB	Sensitivity: 94 dB
Frequency Response: 80 - 4,500 Hz	Frequency Response: 90 - 6,500 Hz	Frequency Response: 95 - 6,500 Hz
Voicel Coil: 1.5"	Voicel Coil: 1.5"	Voicel Coil: 1.5"
Steel Basket – Ferrite Magnet	Steel Basket – Ferrite Magnet	Steel Basket – Ferrite Magnet
Weight: 6.17 Lbs	Weight: 4.63 Lbs	Weight: 3.30 Lbs
Mounting Depth: 3.35"	Mounting Depth: 2.95"	Mounting Depth: 2.36"

TWEETERS

TPT-ST2

4" Super Tweeter	120W / 240W Max Power
Aluminum Diaphragm	Frequency Response: 2,000 - 2,300 Hz
15 Oz Magnet	SPL: 105dB (1W/1M)
1" High Temperature Voice Coil	





COMBOS



TPT-DH100



TPT-DH150



TPT-DH2000

Plastic Horn + Neodymium Compression Driver Plastic Horn + Neodymium Compression Driver Short Aluminium Horn + Compression Driver

200 Watts Continuous Power	200 Watts Continuous Power	400 Watts Continuous Power
100 Watts RMS Power	100 Watts RMS Power	200 Watts RMS Power
Impedance: 8 Ohms	Impedance: 8 Ohms	Impedance: 8 Ohms
Sensitivity: 106 dB	Sensitivity: 104 dB	Sensitivity: 109 dB
Frequency Response: 1.5KHz - 18KHz	Frequency Response: 1.5KHz - 18KHz	Frequency Response: 1.0KHz - 20KHz
1" Phenolic Voice Coil	1" Phenolic Voice Coil	2" Titanium Voice Coil
1" Exit Plastic Horn + Neodymium Driver	1" Exit Plastic Horn + Neodymium Driver	2" Exit Aluminium Horn + Ferrite Driver
Weight: 0.40Lbs	Weight: 1.1 Lbs	Weight: 7.20 Lbs
Mounting Depth: 3.25" (82.5 mm)	Mounting Depth: 2.75" (70 mm)	Mounting Depth: 5.75" (146 mm)

HORNS

TPT-H14-50SLIM

2" Exit Throat
Size: 155mm x 155mm x 75mm
Designed for car door installation

