



P3 Subwoofer Series

Common Features:

- Texture Coat Finish on Stamped Steel Basket • Kapton Voice Coil Former
- Polypropylene Injection Molded Cone • Butyl-Rubber Surround • Nickel Plated Compression 8 ga. Wire Terminal • Suspension Intergrated Tinsel Leads



Model	Size	Power	Impedance	Magnet
P3-10W	10"	2000 Watts	Dual 2Ω	120 oz.
P3-12W	12"	2600 Watts	Dual 2Ω	150 oz.
P3-15W	15"	2800 Watts	Dual 2Ω	180 oz.

P2 Subwoofer Series

Common Features:

- Texture Coat Finish on Stamped Steel Basket • Kapton Voice Coil Former
- Polypropylene Injection Molded Cone • Butyl-Rubber Surround • Nickel Plated Compression 8 ga. Wire Terminal • Suspension Intergrated Tinsel Leads



Model	Size	Power	Impedance	Magnet
P2-10W	10"	1200 Watts	Dual 4Ω	110 oz.
P2-12W	12"	1400 Watts	Dual 4Ω	120 oz.
P2-15W	15"	1600 Watts	Dual 4Ω	140 oz.

P1 Subwoofer Series

Common Features:

- Texture Coat Finish on Stamped Steel Basket • KSV Kapton Voice Coil
- Polypropylene Injection Molded Cone • Butyl-Rubber Surround • Nickel Plated Compression 8 ga. Wire Terminal • Suspension Intergrated Tinsel Leads



Model	Size	Power	Impedance	Magnet
P1-10W	10"	700 Watts	Dual 4Ω	70 oz.
P1-12W	12"	900 Watts	Dual 4Ω	70 oz.
P1-15W	15"	1000 Watts	Dual 4Ω	80 oz.

MOFO Subwoofer Series

Common Features:

- 2.5" Dual 2 ohm 4-Layer Voice Coil • Die-Cast Aluminum Frame • Royal Blue Finish w/Diamond Cut Accents • Non-Pressed Pulp Cone • Polyether Foam Surround • Die Cast Aluminum Voice Coil Heatsink • Nickel Plated 8 gauge Compression Wire Terminals • Vented Pole Piece



Model	Size	Power Max/RMS	Motor Weight
MOFO-122X	12"	2700 Watts/1500 Watts	373 oz.
MOFO-152X	15"	3000 Watts/1700 Watts	373 oz.



THIN Subwoofer (Shallow-Mount)

- 2" Mounting Depth • Proprietary Cast Aluminum Basket • Polypropylene Cone • Aluminum Voice Coil Former • 2" Voice Coil • Semi-Circular Basket Venting • 12 ga. Direct Wire Terminal



Model	Size	Power	Impedance	Magnet
THIN-13	13"	700 Watts	Dual 4Ω	31 oz.

PSQ Subwoofer Series

Common Features:

- 28% more Cone Area than Round Woofer • Stamped Steel Basket w/Rolled Edges • Aluminum Voice Coil Former • Silver Polypropylene Cone • Injection Molded Polypropylene Dust Cap • Multi-Roll NBR Rubber Surround • Vented Back Plate • Suspension Integrated Tinsel Leads



Model	Size	Power	Impedance	Magnet
PSQ-10W	10"	1800 Watts	Dual 4Ω	82 oz.
PSQ-12W	12"	1800 Watts	Dual 4Ω	82 oz.

Midrange Speakers

MID-65

- Midrange/Bass Driver • Heavy Stamped Steel Basket • 1.25" High Temperature Voice Coil • High Strength Magnet • 4 ohm Impedance • 300 Watts

XPS-104

- 4" Midrange Closed Basket (Sold Individually) • .75" Voice Coil • 15 oz. Magnet • 4 ohm Impedance • 120 Watts



XP Speakers

- Black Texture Coat Stamped Steel Frame • Chrome Back Plate • Poly Propylene Injection Cone • Butyl Rubber Surround • 3 ohm Imp. • 1" Silk Midrange (694K) • .75" Silk Tweeter • .5" Silk Super Tweeter (694K/653K/573K)



Model	Size	Type	RMS Power	Magnet
XP-694K	6" x 9"	4-way	420	20 oz.
XP-653K	6.5"	3-way	250	10 oz.
XP-573K	5" x 7"	3-way	270	10 oz.
XP-502K	5.25"	2-way	200	10 oz.
XP-462K	4" x 6"	2-way	200	5.3 oz.
XP-4103K	4" x 10"	3-way	270	10 oz.
XP-402K	4"	2-way	180	5.3 oz.



Pro Audio Neodymium Midrange Speakers

PR.654N – 6.5" - 250 Watts Max, 4 ohm

PR.804N – 8" - 350 Watts Max, 4 ohm



Pro Audio Midrange Speakers

PRO.654 – 6.5" - 170 Watts Max, 4 ohm

PRO.658 – 6.5" - 170 Watts Max, 8 ohm

PRO.804 – 8" - 200 Watts Max, 4 ohm

PRO.808 – 8" - 200 Watts Max, 8 ohm

PRO.104 – 10" - 350 Watts Max, 4 ohm



Components

XP2K-60C

- 6.5" Electro-Plated Injection Molded Cone Mid-Bass • Chrome Basket and Magnet Back Plate • 30 oz. Strontium Magnet • Butyl Rubber Surround • Screw Gold Terminals • 1" Kapton Voice Coil
- 150 Watts • 1" Silk Dome Tweeter • Ferro Fluid Cooled • Neodymium Magnet • 3-Way Mounting • 2-Way Crossover • Impedance: 4 ohm



CPT-60C

- 6.5" Component Speaker 160 Watts MAX
- Black Zirconium Coated Cone • Rubber Surround • 1" Aluminum Voice Coil
- Zolon Coated Low Resonance Basket
- 13mm Super Dome Tweeter • White Terminal Connections • Rubber Magnet Cover • 20 oz. Magnet • Imp: 4 ohm





KP Speaker Series

- Butyl Rubber Surround • Injection Molded Cone or Poly Injected Cone
- Impedance: 4 ohm • Piezo Tweeter or Superior Dome Tweeter



Model	Size	Type	Power Handling
KP-694N	6" x 9"	4-Way	380 Watts
KP-653N	6.5"	3-Way	220 Watts
KP-52N	5.25"	2-Way	180 Watts
KP-42N	4"	2-Way	160 Watts
KP-462N	4" x 6"	2-Way	180 Watts
KP-573N	5" x 7" or 6" x 8"	3-Way	240 Watts

Tweeters



- NB-1**
- 2-Way Mount Tweeter • Built-In Crossover
 - 100 Watts RMS/200 Watts Peak • Niobium Rare Earth Ferroelectric Transducer Magnet
 - Surface/Angle Mount



- NB-2**
- 3-Way Mount Tweeter • Niobium Rare Earth Ferroelectric Transducer Magnet • Built-In Crossover
 - 100 Watts RMS/200 Watts Peak
 - Surface/Angle Mount



- NB-4**
- 3-Way Mount Tweeter • Built in Crossover
 - Niobium Rare Earth Ferroelectric Transducer Magnet • 250 Watts • Swivel/Surface/Angle Mount/Flush Mount • 4 ohm Impedance



- NX-5**
- Bullet Tweeter • Titanium Diaphragm • Cast Aluminum Frame • 1.25" High Temperature Voice Coil • Heavy Stamped Steel Basket
 - High Strength Magnet • 200 Watts • 4 ohm



- NX-6**
- Horn Tweeter • Cast Aluminum Frame • Horn Loaded • 1" Copper Clad Aluminum Voice Coil
 - Ferro Fluid Cooled Voice Coil • 200 Watts
 - 8 ohm Impedance