



## Xtreme 3XL Subwoofer Series



- Z-2 Titanium Non-Pressed Raw Pulp Cone • U-Turn High Roll Treated Foam Surround • Custom CNC Cut, Cast Aluminum Basket • XTRA Large Motor Structure • Pro-lock Input Terminals • CNC Billet Aluminum Trim Ring

Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
<b>3XL-151D</b>	- 15"	1000 Watts/2000 Watts	3" HD Basv	Dual 1Ω	562 oz.
<b>3XL-152D</b>	- 15"	1000 Watts/2000 Watts	3" HD Basv	Dual 2Ω	562 oz.
<b>3XL-121D</b>	- 12"	850 Watts/1700 Watts	3" HD Basv	Dual 1Ω	552 oz.
<b>3XL-122D</b>	- 12"	850 Watts/1700 Watts	3" HD Basv	Dual 2Ω	552 oz.

## Xtreme 2XL Subwoofer Series



- Proprietary COC/Graphite Cone • High Roll Santoprene Surround • Custom CNC Cut, Cast Aluminum Basket • XTRA Large Motor Structures • Pro-lock Input Terminals • CNC Billet Aluminum Trim Ring

Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
<b>2XL-154D</b>	- 15"	500 Watts/1000 Watts	2.5" Basv	Dual 4Ω	312 oz.
<b>2XL-124D</b>	- 12"	450 Watts/900 Watts	2.5" Basv	Dual 4Ω	280 oz.
<b>2XL-104D</b>	- 10"	400 Watts/800 Watts	2.5" Basv	Dual 4Ω	264 oz.

## Xtreme XL Subwoofer Series



- Z-Proprietary 4-layer, Non-pressed Paper, DDC Finish Cone Dynamic Damping Coating (DDC) • High Roll Santoprene Surround • Proprietary Composite Polycarbonate/Glass Fiber Basket • XTRA Large Motor Structures • Chrome Push Terminals

Model	Size	RMS/Peak	Voice Coil	Impedance	Motor
<b>XL-154D</b>	- 15"	500 Watts/1000 Watts	2.5" Vented Basv	Dual 4Ω	250 oz.
<b>XL-124D</b>	- 12"	400 Watts/800 Watts	2" Vented Basv	Dual 4Ω	186 oz.
<b>XL-104D</b>	- 10"	350 Watts/700 Watts	2" Vented Basv	Dual 4Ω	164 oz.
<b>XL-84</b>	- 8"	200 Watts/400 Watts	1.5" Vented Basv	Single 4Ω	116 oz.

– Call your Sales-Rep for Details –  
– Territory Restrictions –



## L Subwoofer Series

- Z-2 Titanium Zirconium Cone • Chrome Domed Backplate
- Power Black Steel Basket • Chrome Push Terminals



Model	Size	Power Handling RMS/Peak	Voice Coil	Impedance	Motor
<b>L-154D</b>	- 15"	500Watts/1000Watts	2.5" KSV	Dual 4Ω	232 oz.
<b>L-124D</b>	- 12"	400Watts/800Watts	2" KSV	Dual 4Ω	180 oz.
<b>L-104D</b>	- 10"	350Watts/700Watts	2" KSV	Dual 4Ω	164 oz.

## M Subwoofer Series

- DDC Non-Pressed Paper Cone • Black Domed Backplate
- Power Black Steel Basket • Chrome Push Input Terminals



Model	Size	Power Handling RMS/Peak	Voice Coil	Impedance	Motor
<b>M-154D</b>	- 15"	425Watts/850Watts	2.5" BASV	Dual 4Ω	220 oz.
<b>M-154</b>	- 15"	425Watts/850Watts	2.5" BASV	Single 4Ω	220 oz.
<b>M-124D</b>	- 12"	350Watts/700Watts	2" BASV	Dual 4Ω	164 oz.
<b>M-124</b>	- 12"	350Watts/700Watts	2" BASV	Single 4Ω	164 oz.
<b>M-104D</b>	- 10"	325Watts/650Watts	2" BASV	Dual 4Ω	158 oz.
<b>M-104</b>	- 10"	325Watts/650Watts	2" BASV	Single 4Ω	158 oz.

## S Thin Subwoofer Series

- Injection Molded Cone • Composite Fiber Basket
- Chrome Push Input Terminals • 3.25" Deep



Model	Size	Power Handling RMS/Peak	Voice Coil	Impedance	Motor
<b>S-12TD</b>	- 12"	300Watts/600Watts	2" KSV	Dual 4Ω	140 oz.
<b>S-12T</b>	- 12"	300Watts/600Watts	2" KSV	Single 4Ω	140 oz.
<b>S-10TD</b>	- 10"	275Watts/550Watts	2" KSV	Dual 4Ω	116 oz.
<b>S-10T</b>	- 10"	275Watts/550Watts	2" KSV	Single 4Ω	116 oz.

## S Subwoofer Series

- 4 Layer Paper/Wool Cone • Black Painted Steel Basket
- Chrome Push Input Terminals



Model	Size	Power Handling RMS/Peak	Voice Coil	Impedance	Motor
<b>S-12D</b>	- 12"	300Watts/600Watts	2" ASV	Dual 4Ω	142 oz.
<b>S-12</b>	- 12"	300Watts/600Watts	2" ASV	Single 4Ω	142 oz.
<b>S-10D</b>	- 10"	275Watts/550Watts	2" ASV	Dual 4Ω	116 oz.
<b>S-10</b>	- 10"	275Watts/550Watts	2" ASV	Single 4Ω	116 oz.



## Xtreme 2XL Series Full Range Speakers

- Pivot Point 1" Silk Dome Swivel Tweeter • 50/50 Wool Blend Cone
- Butyl Rubber Surround • Rigid Tooled Basket with Stainless Steel Finish
- Heavy Motor Structure • PBX Custom Grill

Model	Size	RMS/Peak	Impedance	Magnet
<b>2XL-6902</b>	- 6 x 9"	100 Watts/200 Watts	3 ohms	30 oz.
<b>2XL-6802</b>	- 6 x 8"	75 Watts/150 Watts	3 ohms	14 oz.
<b>2XL-6705</b>	- 6.75"	75 Watts/150 Watts	3 ohms	12 oz.
<b>2XL-6502</b>	- 6.5"	75 Watts/150 Watts	3 ohms	14 oz.
<b>2XL-650T</b>	- 6.5"-Thin	60 Watts/120 Watts	3 ohms	12 oz.
<b>2XL-5202</b>	- 5.25"	60 Watts/120 Watts	3 ohms	12 oz.
<b>2XL-4602</b>	- 4 x 6"	50 Watts/100 Watts	3 ohms	10 oz.
<b>2XL-4002</b>	- 4"	50 Watts/100 Watts	3 ohms	10 oz.



## L Series Full Range Speakers

- Aluminum Dome 3/4" Tweeter (2" PEI Dome Midrange L-6903X)
- Z-2 Titanium Zirconium Cone • Butyl Rubber Surround • Rigid Tooled Basket with Black Powder Coat Finish • Heavy Motor Structure • SEL Tweeter Ring (Sound Expander Lens)

Model	Size	RMS/Peak	Impedance	Magnet
<b>L-6903X</b>	- 6 x 9"	100 Watts/300 Watts	3 ohms	30 oz.
<b>L-6802X</b>	- 6 x 8"	70 Watts/210 Watts	3 ohms	14 oz.
<b>L-6502X</b>	- 6.5"	60 Watts/180 Watts	3 ohms	12 oz.
<b>L-6705X</b>	- 6.75"	60 Watts/180 Watts	3 ohms	12 oz.
<b>L-5202X</b>	- 5.25"	50 Watts/150 Watts	3 ohms	10 oz.
<b>L-4602X</b>	- 4 x 6"	40 Watts/120 Watts	3 ohms	10 oz.



## Xtreme Component Tweeters

- Pivot Point 1" Silk Dome Swivel Tweeter • 50/50 Wool Blend Cone • Butyl Rubber Surround • Rigid Tooled Basket w/Stainless Steel Finish • Heavy Motor Structure • Computer Aided External 2-way Crossover Network • PBX Custom Grill

Model	Size	RMS/Peak	Impedance
<b>2XL-60C</b>	- 6.5"	90 Watts/180 Watts	3 ohms
<b>2XL-50C</b>	- 5.25"	70 Watts/140 Watts	3 ohms



– Call your Sales-Rep for Details –  
– Territory Restrictions –



## S Series Full Range Co-ax Speakers & Components

• DDC Paper Cone • Black Painted Steel Basket



Model	Size	Power Handling RMS/Peak	Tweeter	Magnet
<b>S-693</b>	6 x 9" 3-Way	70Watts/210Watts	0.75" & 2" Mylar Cone	20 oz.
<b>S-682</b>	6 x 8" (5x7" Compatible)	60Watts/180Watts	0.75" Silk Dome	10 oz.
<b>S-412</b>	4 x 10"	50Watts/150Watts	0.75" Silk Dome	10 oz.
<b>S-675</b>	6.75"	50Watts/150Watts	0.75" Silk Dome	10 oz.
<b>S-652</b>	6.5"	50Watts/150Watts	0.75" Silk Dome	10 oz.
<b>S-65T</b>	6.5" (Thin)	45Watts/135Watts	0.75" Silk Dome	10 oz.
<b>S-522</b>	5.25"	40Watts/120Watts	0.75" Silk Dome	8 oz.
<b>S-462</b>	4 x 6"	35Watts/105Watts	0.75" Silk Dome	6 oz.
<b>S-402</b>	4"	35Watts/105Watts	0.75" Silk Dome	6 oz.
<b>S-352</b>	3.5"	30Watts/90Watts	0.75" Silk Dome	4 oz.

## Component Kits and Tweeters



Model	Size	Power Handling RMS/Peak	Tweeter	Magnet
<b>S-6C</b>	6.5" Component w/X-over Kit	70Watts/210Watts	1.0" Silk Dome	10 oz.
<b>S-5C</b>	5.25" Component w/X-over Kit	50Watts/150Watts	1.0" Silk Dome	10 oz.
<b>S-1S</b>	1"	50Watts RMS/100Watts Peak	1" Silk Dome	Neodymium
<b>S-1ZT</b>	1"	100Watts RMS/200Watts Peak	1" Zirconium Super Tweeter	

## Xtreme Tweeters

• Pivoting Tweeters w/Composite Surround • Compact Computer Optimized Acoustic Crossover Network • Flush, Angle and Surface Mount Kit

Model	Size	RMS/Peak	Impedance
<b>3XL-2S</b>	1.25" - Pure Silk	60 Watts/120 Watts	4 ohms
<b>2XL-1T</b>	1" - Titanium	50 Watts/100 Watts	4 ohms

