



Punch 'P1' Subwoofers

- Flex Fit Basket Design • Stamp-Cast Basket w/Integrated Spider Venting
- Kevlar Fiber Reinforced Paper Cone • Soft Touch ABS Trim Ring with Optional Grille

Model	Size	Impedance	Capacity
P1S4-8	8"	4 ohm SVC	200W RMS/400W Peak
P1S8-8	8"	8 ohm SVC	200W RMS/400W Peak
P1S4-10	10"	4 ohm SVC	250W RMS/500W Peak
P1S8-10	10"	8 ohm SVC	250W RMS/500W Peak
P1S4-12	12"	4 ohm SVC	250W RMS/500W Peak
P1S8-12	12"	8 ohm SVC	250W RMS/500W Peak
P1S4-15	15"	4 ohm SVC	250W RMS/500W Peak
P1S8-15	15"	8 ohm SVC	250W RMS/500W Peak



Punch 'P2' Subwoofers

- VAST (Vertical Attach Surround Technique) • Flex Fit Basket Design
- StampCast™ Frame Structure • 2.25" Copper Clad Aluminum Voice Coil
- Kevlar Fiber Reinforced Paper Cone • Diamond Cut Cast Aluminum Trim Ring with Optional Grille

Model	Size	Impedance	Capacity
P2D2-8	8"	2 ohm DVC	250W RMS/500W Peak
P2D4-8	8"	4 ohm DVC	250W RMS/500W Peak
P2D2-10	10"	2 ohm DVC	300W RMS/600W Peak
P2D4-10	10"	4 ohm DVC	300W RMS/600W Peak
P2D2-12	12"	2 ohm DVC	400W RMS/800W Peak
P2D4-12	12"	4 ohm DVC	400W RMS/800W Peak
P2D2-15	15"	2 ohm DVC	400W RMS/800W Peak
P2D4-15	15"	4 ohm DVC	400W RMS/800W Peak



Punch 'P3' Subwoofers

- VAST (Vertical Attach Surround Technique) • Flex Fit Basket Design
- StampCast™ Frame Structure • 2.25" Copper Clad Aluminum Voice Coil
- Thermal Anodized Aluminum Cone • Diamond Cut Cast Aluminum Trim Ring with Optional Grille

Model	Size	Impedance	Capacity
P3D2-10	10"	2 ohm DVC	500W RMS/1000W Peak
P3D4-10	10"	4 ohm DVC	500W RMS/1000W Peak
P3D2-12	12"	2 ohm DVC	600W RMS/1200W Peak
P3D4-12	12"	4 ohm DVC	600W RMS/1200W Peak
P3D2-15	15"	2 ohm DVC	600W RMS/1200W Peak
P3D4-15	15"	4 ohm DVC	600W RMS/1200W Peak



Punch 'P3' Shallow Subwoofers

- Die-Cast Aluminum Basket with Spider Venting • Kevlar Fiber Reinforced Paper Cone • Linear Spider with Stitched 16 AWG Tinsel Leads • Ultra Shallow Design
- Diamond Cut Cast Aluminum Reversible Trim Ring with Optional Grille

Model	Size	Impedance	Capacity
P3SD210	10"	2 ohm DVC	300W RMS/600W Peak
P3DD410	10"	4 ohm DVC	300W RMS/600W Peak
P3SD212	12"	2 ohm DVC	400W RMS/800W Peak
P3SD412	12"	4 ohm DVC	400W RMS/800W Peak



Authorized Dealers Only



Power Subwoofers (200 Series)

- High Excursion Thermoplastic Rubber Surround • Dual Die-Cast Aluminum Baskets with Spider Venting • Cast Aluminum Reversible Mount Ring • Aluminum Parabolic Cone • Aluminum Voice Coil



Model	Size	Impedance	Capacity	Motor
T2D212	12"	2 ohm DVC	1000W RMS/2000W Peak	-
T2D412	12"	4 ohm DVC	1000W RMS/2000W Peak	-
T2D215	15"	2 ohm DVC	1000W RMS/2000W Peak	-
T2D415	15"	4 ohm DVC	1000W RMS/2000W Peak	-
T212D2	12"	2 ohm DVC	1000W RMS/2000W Peak	304 oz.
T212D4	12"	4 ohm DVC	1000W RMS/2000W Peak	304 oz.
T215D2	15"	2 ohm DVC	1000W RMS/2000W Peak	304 oz.
T215D4	15"	4 ohm DVC	1000W RMS/2000W Peak	304 oz.

Power Subwoofers

- High Excursion Thermo-Rubber Surround • Anodized Aluminum Voice coil Former/Copper Clad Aluminum Wire • Massive Double Stacked Magnet Motor Assembly



Model	Size	Impedance	Capacity	Motor
T1D210	10"	2 ohm DVC	600W RMS/1200W Peak	-
T1D410	10"	4 ohm DVC	600W RMS/1200W Peak	-
T1D212	12"	2 ohm DVC	600W RMS/1200W Peak	-
T1D412	12"	4 ohm DVC	600W RMS/1200W Peak	-
T110D2	10"	2 ohm DVC	600W RMS/1200W Peak	102 oz.
T110D4	10"	4 ohm DVC	600W RMS/1200W Peak	102 oz.
T112D2	12"	2 ohm DVC	600W RMS/1200W Peak	124 oz.
T112D4	12"	4 ohm DVC	600W RMS/1200W Peak	124 oz.
T115D2	15"	2 ohm DVC	600W RMS/1200W Peak	220 oz.
T115D4	15"	4 ohm DVC	600W RMS/1200W Peak	220 oz.

Prime Subwoofers

- 18 AWG Stamped Steel Frame • 12 AWG Compression Terminals
- Parabolic Polypropylene Cone • Optimized for Sealed Enclosures
- Available in Single (4 ohm) and Dual (2 ohm) Sealed Enclosures



Model	Size	RMS Watts/Peak Watts	ohms
R1S410	10" Subwoofer	150W/300W	4
R1S412	12" Subwoofer	150W/300W	4

Authorized Dealers Only

– Territory Restrictions –



Prime Coaxials

- 18 AWG Stamped Steel Frame • Mica Injected Polypropylene Cone • Includes Grilles and Mounting Hardware • 1/2" (13mm) Mylar Balance Dome Tweeter



Model	Description	RMS Watts/Peak Watts
R152	5.25" Full Range Coaxial	35W/70W
R1653	6.5" Full Range 3-Way	40W/80W
R1682	6 x 8" Full Range 2-Way	50W/100W
R1693	6 x 9" Full Range 3-Way	60W/120W

Punch Coaxials

- Common Features:
- Titanium Composite Dome Tweeter
 - Mica Injected Polypropylene Cone



Model	Size	Type	Power	Grilles
P132	3.5"	2-Way	20W RMS/40W Peak	Yes
P142	4"	2-Way	30W RMS/60W Peak	Yes
P152	5.25"	2-Way	40W RMS/80W Peak	Yes
P1S652	6.5"	2-Way	55W RMS/110W Peak	Yes
P1653	6.5"	3-Way	60W RMS/120W Peak	Yes
P1462	4 x 6"	2-Way	35W RMS/70W Peak	-
P1572	5 x 7"	2-Way	60W RMS/120W Peak	-
P1683	6 x 8"	3-Way	65W RMS/130W Peak	-
P1692	6 x 9"	2-Way	75W RMS/150W Peak	Yes
P1694	6 x 9"	4-Way	75W RMS/150W Peak	Yes

Power Coaxials

- Common Features:
- Polyurethane Surround • .75" Aluminum Dome Tweeter • Cold Rolled Steel Vented • Injection Molded Polypropylene Cone • Proprietary



Model	Size/Type	Power	Grilles
T142	4" - 2-Way	40W RMS/80W Peak	X
T152	5.25" - 2-Way	60W RMS/120W Peak	X
T1S652	6.5" - 2-Way	70W RMS/140W Peak	X
T1652	6.5" - 2-Way	75W RMS/150W Peak	X
T1462	4 x 6" - 2-Way	40W RMS/80W Peak	-
T1572	5 x 7" - 2-Way	75W RMS/150W Peak	-
T1682	6 x 8" - 2-Way	75W RMS/150W Peak	-
T1692	6 x 9" - 2-Way	100W RMS/200W Peak	X
T1693	6 x 9"/1" - 2-Way	110W RMS/220W Peak	X

Authorized Dealers Only

— Territory Restrictions —