## **X3 Subwoofer Series**

Model	Size	Burp Power (watts)	RMS Power (watts)	Voice Coil Configuration
X3-122 -	12"	95V (9000w)	71V (5000w)	4" DVC 2Ω
X3-152 -	15"	100V (10000w)	77V (6000w)	4" DVC 2Ω
X3-182 -	18"	105V (11000w)	84V (7000w)	4" DVC $2\Omega$



## **SPLX Subwoofer Series**

- Cast Aluminum Frame 10ga Hard-Wired Speaker Leads Coated Paper Cone
- UV Coated Foam Surround Aluminum Coil Former

Model	Size	RMS Power (watts)	Voice Coil Configuration
SPLX-122HX	- 12"	1000	3" Dual 2Ω
*SPLX-122HF	- 12"	1000	3" Dual $2\Omega$
SPLX-152HX	- 15"	1250	3" Dual $2\Omega$
*SPLX-152HF	- 15"	1000	3" Dual $2\Omega$





## Tarantula Subwoofer Series

 Proprietary 7-Piece Cast Aluminum Basket • Dual 4-ohm 2.5" Voice Coil • Translucent Cone w/Etched Logos • Spoked Stiffening Sub-Cone • High-Roll Rubber Surround • Twin Progressive Spider Suspension • Concealing Trim Ring Included

Model	Size	RMS Power (watts)	<b>Voice Coil Configuration</b>		
T6-12	- 12"	900	2.5" Dual $4\Omega$		
T6-15	- 15"	1000	2.5" Dual 40		



## Tarantula TSQ (Square) Subwoofer Series

• Translucent TPX Honeycomb Cone • Aluminum Coil Former • Texture Coat on Stamped Steel Frame • Multi-Roll Rubber Surround

Model		Size		RMS Power (watts)	<b>Voice Coil Configuratio</b>		
	TSQ-102	_	10"	500	2" Dual $2\Omega$		
	<b>TSQ-104</b>	_	10"	500	2" Dual $4\Omega$		
	<b>TSQ-122</b>	_	12"	650	2" Dual $2\Omega$		
	TSQ-124	_	12"	650	2" Dual 4Ω		



## XXX **Subwoofer Series**

 Cast Basket
 Non-Pressed UV Coated Cone
 Thick & Dense Foam Surround • Chrome Top & Bottom Plated • Copper Clad Aluminum Voice Coil • Integrated Tinsel Leads • Dual Nomex Spiders

Model	Size	RMS Power	Impedance	Magnet
XXX-15	15"	8500 Watts	4 x 1Ω	475 oz.
XXX-18	18"	10000 Watts	4 x 1Ω	475 oz.

## Reference R1 **Subwoofer Series**

- Aluminum Cone & Dust Cap Dual Spiders for Added Strength • High Roll Surround for Extended Excursion
- Easy-to-Install Re-cone Kits Available

Model	Size	RMS Power	<b>Voice Coil Configuration</b>		
R1-12	12"	800 Watts	3" Dual 2 ohm		
R1-15	15"	900 Watts	3" Dial 2 ohm		



### **Common Features:**

- Cast Aluminum Basket Hand Laid Pulp Paper Cone 1-Piece Gasket Tall Rubber Surround • Large PP Injected Dust Cap • Vented Back Plate
  • Dual Stacked Magnet Assembly

Model	Size	RMS Power	Impedance	Magnet
RW-10	10"	500 Watts	Dual 4Ω	100 oz.
RW-12	12"	600 Watts	Dual $4\Omega$	120 oz.

## Stealth-13 Subwoofer

### **Common Features:**

- Proprietary Cast Aluminum Basket Inverted Motor Assembly
- Solid Aluminum Cone 5" Voice Coil 12ga. Direct Wire Terminal
- 2" Mounting Depth Semi-Circular Basket Venting

Model	Size	RMS Power	Impedance	Magnet
STEALTH-13	13.25"	200 Watts	-	-





**Authorized Dealers Only** 

- Call your Sales-Rep for Details -

- Territory Restrictions -

## **Rubicon Subwoofer Series**

Texture Coat Finish on Stamped Steel Basket • NBR-Rubber Surround • Polypropylene Injection Molded Cone • Dual 4 ohm Keisv Kapton Voice Coils • Vented Back Plate

•				
	Model	Size	RMS Power	Impedance
	RBW-10	10"	450 Watts	2" Dual 4Ω
	<b>RBW-12</b>	12"	600 Watts	2.5" Dual $4\Omega$
	RBW-15	15"	800 Watts	2 5" Dual 4O

## **Picasso Subwoofer Series**

**Common Features:** 

 Texture Coat Finish on Stamped Steel Basket
 NBR-Rubber Surround • Polypropylene Injection Molded Cone • KSV Kapton **Voice Coils • Suspension Integrated Tinsel Leads** 

Model	Size	RMS Power	Impedance
PXW-10	10"	350 Watts	2" Dual 4Ω
PXW-10/2	10"	350 Watts	2" Dual $2\Omega$
PXW-12	12"	400 Watts	2" Dual $4\Omega$
PXW-12/2	12"	400 Watts	2" Dual $2\Omega$
PXW-15	15"	500 Watts	2.5" Dual $4\Omega$
PXW-15/2	15"	500 Watts	2.5" Dual $2\Omega$

## **T5 Subwoofer Series**

Cast Aluminum Basket • Hand Laid Pulp Paper Cone • One-Piece Gasket/Tall Rubber Surround • Dual 2 ohm 3" Aluminum Voice Coil
 Vented Back Plate • Nickel Plated Push Terminals

Model	Size	RMS Power	Impedance	Magnet
T5-10	10"	800 Watts	Dual 2Ω	160 oz.
T5-12	12"	900 Watts	Dual $4\Omega$	200 oz.
T5-15	15"	1000 Watts	Dual $2\Omega$	250 oz.



### **Authorized Dealers Only**

# Tarantula Full Range Speakers Common Features:

 Zolon Coated Stamped Steel Basket • 1" Kapton Coil Former • Butyl Rubber Surround • 1" Swivel Sild Dome Tweeter • Black Zirconium Cone

•	Bi-Amn	Canability	• (	Conex	Spider	• F	Passive	Cross	over I	ncluded	

Model	Size	RMS Power	Impedance	Magnet
SST6.9	6x9" 2-Way	150 Watts	3Ω	22 oz.
SST6.5	6x5" 2-Way	120 Watts	3Ω	12 oz.
SST5.7	5x7" 2-Way	130 Watts	3Ω	12 oz.
SST5.2	5.25" 2-Way	100 Watts	3Ω	10 oz.
SST4.6	4x6" 2-Way	100 Watts	3Ω	10 oz.
SST4.0	4" 2-Way	85 Watts	3Ω	8 oz.

## **Rubicon Full** Range Speakers Common Features:


• Stamped Steel Basket • TPU Surround • 1" Kapton Coil Former

• 1" Polymide Tweeter • Carbon Injection Cone • Polymide Midrange and Tweeter • 2" Polymide Midrange (693, 653, and 573)

Model	Size	RMS Power	Impedance	Magnet
<b>RBT-693</b>	6x9" 3-Way	140 Watts	3Ω	25 oz.
<b>RBT-653</b>	6x5" 3-Way	100 Watts	3Ω	15 oz.
RTB-573	5x7" 3-Way	120 Watts	3Ω	15 oz.
<b>RBT-502</b>	5.25" 2-Way	85 Watts	3Ω	12 oz.
<b>RBT-462</b>	4x6" 2-Way	85 Watts	3Ω	10 oz.
<b>RBT-402</b>	4" 2-Way	70 Watts	3Ω	10 oz.

## Picasso Full **Range Speakers**

Stamped Steel Basket • Butyl-Rubber Surround • 1" Aluminum
 Coil Former • 1" Mylar Tweeter • Carbon Injection Cone • Mylar
 Midrange and Tweeter • 2" Mylar Midrange (693)



### **Authorized Dealers Only**

- Call your Sales-Rep for Details -

Arachnid Subwoofer,

SW-12SE

 Dual 4 ohm 12" Subwoofer • 500W Max/250W RMS • Black Zirconium Coated Injection Cone • 2" KSV Kapton Voice Coil
 NBR-Rubber Surround • Nickel Plated 8 gauge Compression

 NBR-Rubber Surround
 Nickel Plated 8 gauge Compression Wire Terminal
 Suspension Integrated Tinsel Leads
 Steel Basket
 Vented Pole Piece



# Arachnid Full Range Coaxial Speakers

**Common Features:** 

 White Zirconium Coated Cone • Zolon Coated Low Resonance Basket • Rubber Surround • 1" Aluminum Voice Coil • 13mm Super Dome Tweeter • White Terminal Connections • Rubber Magnet Cover • Impedance: 4 ohm

Model	Size	Power Handling	Magnet
SF-652T	6.5" 2-Way	60 Watts/RMS	5.4 oz.
SF-693T	6x9" 3-Way	100 Watts/RMS	25 oz.



SC-6T

 6.5" Component Speaker • 80 Watts RMS • Zolon Coated Low Resonance Basket • Rubber Surround • White Zirconium Coated Cone • Impedance: 4Ω • 1" Aluminum Voice Coil • 13mm Super Dome Tweeter • White Terminal Connections • 20 oz Magnet

Rubber Magnet Cover



## Hi-Volume Components When "LOUD" just isn't loud enough... SoundStream

When "LOUD" just isn't loud enough... SoundStream brings you the "Pro Series" Drivers to enhance the Volume Level of any System. With 3 Mid-Bass Models & 2 Tweeters, you can Design your System to be heard while maintaining your music Clean and Pleasant. Sleek yet Obnoxiously Loud.



Model	<b>Max Power Handling</b>	Voice Coil	Impedance	<b>Magnet Weight</b>
SST-05	100 Watts	1" Alum/Mag	4	NEO
SST-22	100 Watts	1.75" Alum/Mag	4	13.6 oz.
SM16-90	120 Watts	1.5"	8	30.87 oz.
SM8-100	160 Watts	1.5"	8	38.9 oz.
SST-80/4	300 Watts	1.5"	4	39 oz.
SST-654N	250 Watts	1.5"	4	NEO
SST-804N	350 Watts	1.5"	4	NEO
SST-104	450 Watts	2"	4	50 oz.
SM-104	350 Watts	2"	4	33 oz.
SM-124	400 Watts	2"	4	50 oz.

### **Authorized Dealers Only**

- Call your Sales-Rep for Details -

- Territory Restrictions -



## **Pro Audio**

Model	Size	<b>Max Power Handling</b>	Impedance
SST-20 -	Horn Tweeter	90 watts	4 ohm
SME.654 -	6.5"	170 watts	4 ohm
SME.658 -	6.5"	170 watts	8 ohm
SME.654P -	6.5"	170 watts	4 ohm
SME.654N -	6.5"	250 watts	4 ohm
SME.658N -	8"	250 watts	8 ohm
SME.574 -	5"x7"	170 watts	4 ohm
SME.694 -	6"x9"	185 watts	4 ohm
SME.804 -	8"	200 watts	4 ohm
SME.808 -	8"	200 watts	8 ohm
SM.804N -	8"	350 watts	4 ohm
SM.808N -	8"	350 watts	8 ohm
SME.104 -	10"	350 watts	4 ohm



## **Audio Accessories Tweeters**

- TWT.2

   1" Horn Loaded Titanium Tweeter

   Rated Input Power: 120W Flush
- Mount Aluminum Housing 12dB/ Octave Passive Crossover Included Impedence: 4Ω • Ferrofluid Cooled
- Neodymium Magnet

Mounting: Flush/Surface and Surface Angle • Rated Input Power: 110 Watts • Impedance:



- TWS.3
   1" PEI Dome Tweeter Impedance: 4 ohm • Adjustable Eyeball Design
- 12 dB In-Line Crossover Network
   Tri-Mounting: Flush/Surface/Surface
  Angle Rated Input Power: 110W



### **TWS.4**

- Tantalum 2-way Mount Tweeter
   Polished Aluminum Housing
   12 dB In-Line Crossover Network
   Rated Input Power: 110 Watts

- Impedance: 4 ohm



## **Audio Accessories**

## **Woofer Grill**

**GRILL-10X GRILL-12X GRILL-15X** 

• Chrome Plated Cast Aluminum Tarantula Woofer Grill



### **Authorized Dealers Only**

- Call your Sales-Rep for Details -

Reference Components

• 6.5" Mid-Woofer • Cast Aluminum Basket • Butyl Rubber Surround • 4 ohm • 3" Voice Coil • 25mm Silk Dome • Chrome Motor Cover • Aluminum Voice Coil Former • 2-Way Passive Network • Ferrofluid Cooled • Neodymium

Tweeters Magnets • Nickle Plated Push Terminals





Model **Max Power** Crossover **Magnet Weight Voice Coil** TRC-60C 1.25" 200Watts 12/dB



15 oz.

## **Picasso Compone**

- 6.5" Mid-Woofer Brushed Stainless Steel Finish Stamped Steel Basket
- NBR Rubber Surround 1" Teflon/Silk Dome with Resin CoatingTweeters
- 1" Copper Voice Coil Passive Crossover Ferrofluid Cooled Neodymium Tweeters Magnets • Nickle Plated Binding Posts



# Rubicon Components - 6.5" Mid-Woofer • Die-Cast Basket with Diamond Cut • Cast Aluminum

- Basket Polypropylene Cone Butyl Rubber Surround 1" Silk Dome Tweeter
   Passive 12dB Crossover w/Tweeter Protection Ferro Fluid Tweeter Cooling
- Vented Voice Coil Former Neodymium Tweeters Magnets

